



The Go4 Analysis Framework **Reference Manual v5.2**

J.Adamczewski-Musch, M.Al-Turany, S.Augustin, D.Bertini, H.G.Essel, S. Linev
9 January 2017

The Go4 Analysis Framework Reference Manual v5.2.....	1
1 Go4 analysis framework method reference	7
AddAnalysisCondition (TGo4Condition* con, const char* subfolder):	7
AddAnalysisStep(TGo4AnalysisStep* nextstep):	7
AddCanvas (TCanvas* can, const char* subfolder):.....	8
AddDynamicHistogram(const char* name, const char* histo, const char* hev _x , const char* hmem _x , const char* hev _y , const char* hmem _y , const char* hev _z , const char* hmem _z , const char* condition, const char* cev _x , const char* cmem _x , const char* cev _y , const char* cmem _y):	9
AddHistogram(TH1* his, const char* subfolder, Bool_t replace):	10
AddObject(TNamed* ob, const char* subfolder, Bool_t replace):	11
AddParameter(TGo4Parameter* par, const char* subfolder):.....	12
AddPicture (TGo4Picture* pic, const char* subfolder):.....	12
AddTree(TTree* mytree, const char* subfolder)	13
AddTreeHistogram(const char* hisname, const char* treename, const char* varexpr TCut selection):	14
AutoSave():	15
ClearObjects(const char* name):.....	15
CloseAnalysis():	16
DeleteObjects(const char* name):	16
ExecuteLine(const char* name, Int_t* errcode=0).....	17
ExecutePython(const char* name, Int_t* errcode=0).....	17
ExecuteScript(const char* name)	18
Export(TObject* ob, Go4Export_t filter)	18
GetAnalysisCondition(const char* name).....	19
GetAnalysisStep(const char* name).....	19
GetCanvas(const char* name)	20
GetEventStructure(const char* name):.....	20
GetHistogram(const char* name)	21
GetInputEvent(const char* stepname):.....	21
GetObject(const char* name, const char* topfolder)	22
GetOutputEvent(const char* stepname):	22
GetOutputEvent():	23
GetParameter(const char* name).....	23
GetPicture(const char* name)	24
GetTree(const char* name)	24
InitEventClasses():	25
TGo4Analysis::Instance():.....	25
IsAutoSaveOn():.....	26
IsAutoSaveFileChange():	26
IsBatchMode():.....	27
IsClientMode():	27
IsInitDone():	28
IsKeepInputEvent ():	28
IsKeepOutputEvent ():.....	29
IsNewInputFile():	29
IsRunning():.....	30
IsServerMode():.....	30
LoadObjects (const char* filename):	31
LoadStatus (const char* filename):	31
TGo4Log::LogfileEnable (Bool_t on):.....	32
TGo4Log ::Message (Int_t prio, const char* text,...):	32
TGo4Log::OpenLogfile (const char* filename, const char* headercomment, Bool_t appendmode):	33
TGo4Log::OutputEnable (Bool_t on):	34
TGo4Log::SetIgnoreLevel (Int_t level):.....	34
MakeBoxCond(const char* fullname, Double_t cx, Double_t cy, Double_t a1, Double_t a2, Double_t theta, const char* HistoName) :.....	36

MakeCircleCond(const char* fullname, Int_t npoints, Double_t cx, Double_t cy, Double_t r, const char* HistoName) :	37
MakeEllipseCond(const char* fullname, Int_t npoints, Double_t cx, Double_t cy, Double_t a1, Double_t a2, Double_t theta, const char* HistoName) :	38
MakeParameter(const char* fullname, const char* classname, const char* newcmd):	39
MakePolyCond(const char* fullname, Int_t npoints, Double_t (*points) [2], const char* HistoName, Bool_t shapedcond) :.....	40
MakeTH1 (char type, const char* fullname, const char* title, Int_t nbinsx, Double_t xlow, Double_t xup, const char* xtitle, const char* ytitle) :	41
MakeTH2 (char type, const char* fullname, const char* title, Int_t nbinsx, Double_t xlow, Double_t xup, Int_t nbinsy, Double_t ylow, Double_t yup, const char* xtitle, const char* ytitle, const char* ztitle) :	42
MakeWinCond(const char* fullname, Double_t xmin, Double_t xmax, const char* HistoName) : 43	
MakeWinCond(const char* fullname, Double_t xmin, Double_t xmax, Double_t ymin, Double_t ymax, const char* HistoName) :	43
Message (Int_t prio, const char* text,...):	44
NewStepProcessor (const char* name, TGo4EventProcessorParameter* par):	45
NewStepSource (const char* name, TGo4EventSourceParameter* par):	46
NewStepStore (const char* name, TGo4EventStoreParameter* par):	46
NextMatchingObject (const char* expression, const char* foldername, Bool_t reset):	47
Print(Option_t* opt):	48
PrintConditions(const char* expression):	48
PrintDynamicList():	49
PrintHistograms(const char* expression):	49
Process():	50
ProtectObjects(const char* name , const Option_t* flags):	50
RemoveAnalysisCondition(const char* name)	51
RemoveCanvas(const char* name).....	52
RemoveDynamicEntry(const char* entryname, const char* listname).....	52
RemoveHistogram(const char* name, Bool_t del)	53
RemoveObject(const char* name, Bool_t del)	53
RemoveParameter(const char* name)	54
RemovePicture(const char* name)	54
RemoveTree(TTree* tree)	55
RunImplicitLoop(Int_t times):	55
SaveStatus (const char* filename):	56
SendObjectToGUI (TNamed* ob):	56
SetAnalysisCondition (const char* name, TGo4Condition* con. Bool_t counter):.....	57
SetAutoSave(Bool_t on):	58
SetAutoSaveFile (const char* filename, Bool_t overwrite, Int_t compr):	58
SetAutoSaveFileChange (Bool_t on):	59
SetAutoSaveInterval (Int_t seconds):	60
SetDynListInterval (Int_t val):	60
SetFirstStep (const char* name):	61
SetKeepInputEvent (Bool_t val=kTRUE):	62
SetKeepOutputEvent (Bool_t val=kTRUE):	62
SetLastStep (const char* name):	63
SetMakeWithAutosave(Bool_t on)	63
SetParameter (const char* name, TGo4Parameter* par):	64
SetPicture (const char* name, TGo4Picture* pic):	65
SetRunning(Bool_t on):	65
SetStepChecking (Bool_t on):	66
SetStepStorage (const char* name, Bool_t on):	66
ShowEvent(const char* name, Bool_t isoutput):	67
StoreCondition(const char* stepname, TGo4Condition* con):	68
StoreFitter(const char* stepname, TGo4Fitter* fit):	68
StoreFolder(const char* stepname, TFolder* fold):	69
StoreFolder(const char* stepname, const char* foldername):	69
StoreParameter(const char* stepname, TGo4Parameter* par):	70

UserEventFunc():	71
UserPreLoop():	71
UserPostLoop():	72
WaitForStart():	73
2 GUI Macro Interface Documentation	74
2.1 Introduction	74
2.2 TGo4AbstractInterface Class Reference	75
2.2.1 Public Member Functions	75
2.2.2 Static Public Member Functions	76
2.2.3 Member Function Documentation	77
3 Index	87

1 Go4 analysis framework method reference

In the following, the usable methods of the analysis framework classes are described systematically in alphabetical order. The base classes containing each method are listed in the **Classes** field. The methods of TGo4Analysis, e.g., are available from within the user analysis class, or they may be called externally in the MainUserAnalysis executable (batch mode). The methods of TGo4EventProcessor, e.g., may be called within the user event processor directly. In macros executed in analysis pointer **go4** is a reference to TGo4Analysis::Instance().

AddAnalysisCondition (TGo4Condition* con,
const char* subfolder):

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Register a condition to the Go4 framework. The condition will be visible in the Go4GUI after this call, i.e. it can be edited at the GUI view panel. After this call, Go4 adopts the condition, so the user must not delete the condition object in the destructor! Registered conditions are placed in the TFolder Go4/Conditions which is also saved in the Go4 autosave-file when the analysis is closed, or when [AutoSave\(\)](#) is called. Optionally, a subfolder of Go4/Conditions may be specified where the histogram shall be located. If condition of the same name already existed in the specified folder, the old condition is deleted and replaced by the new condition con.

Arguments:

TGo4Condition* con	Pointer to conditions that shall be registered. Condition is adopted by Go4.
const char* subfolder	Name of the subfolder of Go4/Conditions where condition shall be placed. If not specified (default), condition will be put directly under Go4/Conditions.

Return value:

Bool_t: kTRUE if con was registered. kFALSE if argument con was null..

Visibility:

public

Example of usage:

```
TGo4WinCond* cond= new TGo4WinCond("window1","ADC1",200, 800);  
AddAnalysisCondition(cond);
```

AddAnalysisStep(TGo4AnalysisStep* nextstep):

Classes: TGo4Analysis

Description:

Register analysis step to the Go4 framework. The analysis step object must have been created before. The order of calling this method defines the processing order of the analysis steps, i.e. the first step that was registered will be processed first. **Note that there is currently no way to remove an analysis step from the analysis once it was added!**

Arguments:

TGo4AnalysisStep* nextstep: Pointer to instance of analysis step class. This object is adopted from the framework after calling this function.

Return value:

Bool_t: kTRUE if adding nextstep was successful..

Visibility:

public:

Example of usage:

```
TGo4EventSourceParameter* sopar= new TGo4MbsSourceParameter("listmode.lmd");
TGo4EventStoreParameter* stpar= new TGo4FileStoreParameter("out.root");
TGo4AnalysisStep* step1 = new TGo4AnalysisStep("Unpack",sopar, stpar, 0);
AddAnalysisStep(step1);
```

AddCanvas (TCanvas* can, const char* subfolder):

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Register a ROOT TCanvas to the Go4 framework. Go4 adopts the TCanvas, so the user must not delete the canvas object in the destructor! Registered TCanvas are placed in the TFolder Go4/Canvases which is also saved in the Go4 autosave-file when the analysis is closed, or when [AutoSave\(\)](#) is called. Optionally, a subfolder of Go4/Canvases may be specified where the TCanvas shall be located. If canvas of the same name already existed in the specified folder, the new canvas will not be registered.

Arguments:

TCanvas* can Pointer to canvas that shall be registered. Canvas is adopted by Go4.
const char* subfolder Name of the subfolder of Go4/Canvases where canvas shall be placed. If not specified (default), canvas will be put directly under Go4/Canvases.

Return value:

Bool_t: kTRUE if can was registered. kFALSE if canvas of same name already existed.

Visibility:

public

Example of usage:

```
TCanvas* c = new TCanvas("positions","x-y-z-n");
c->Divide(2,2);
AddCanvas(c);
```



```

AddDynamicHistogram(const char*   name,
                    const char*   histo,
                    const char*   hevX,
                    const char*   hmemX,
                    const char*   hevY,
                    const char*   hmemY,
                    const char*   hevZ,
                    const char*   hmemZ,
                    const char*   condition,
                    const char*   cevX,
                    const char*   cmemX,
                    const char*   cevY,
                    const char*   cmemY ):

```

Classes: TGo4Analysis

Description:

Add (create) new dynamic histogram entry which connects an existing histogram with existing condition and data. Dynamic entry is specified by name. Histogram histo will be searched in registered histograms folder, condition in conditions folder. If condition is true or not existing (condition=0), histogram will be filled from the values that are found in registered eventstructure classes of names evx, evy, evz at the data members of names memx, memy, memz, for the three coordinate axes, respectively. Histogram dimension is checked against given values. Pointers to the objects and data structures that are specified by name are searched once on analysis initialization. Note that this dynamic entry is processed event-by-event, in contrast to the dynamic treehistogram entry (see [AddTreeHistogram\(\)](#)), which uses a TTree::Draw every dynlistinterval. However, this dynamic histogram entry works without any TTree. Addresses of datamembers are searched from ROOT TClass information, values are casted and filled directly to histogram. Only data from valid events are filled into histogram. Datamembers of the following types are currently supported: Float_t, Double_t, Int_t, Short_t, Char_t, Long_t, UInt_t, UShort_t, UChar_t, ULong_t, Bool_t.

Arguments:

const char* name	Name of the dynamic entry. This name will show up in the dynamic histograms display on the gui..
const char* histo	Name of the registered histogram to be filled. May contain full pathname relative to the histograms folder, separated by slash “/”.
const char* hevX	Name of the registered eventstructure object that contains the data to be filled in x coordinate.
const char* hmemX	Name of the datamember of eventstructure class that contains the data to be filled in x coordinate.
const char* hevY	Name of the registered eventstructure object that contains the data to be filled in y coordinate. If zero (default), only one dimensional histogram will be used.
const char* hmemY	Name of the datamember of eventstructure class that contains the data to be filled in y coordinate . If zero (default), only one dimensional histogram will be used.
const char* hevZ	Name of the registered eventstructure object that contains the data to be filled in z coordinate. If zero (default), only one/two dimensional histogram will be used.
const char* hmemZ	Name of the datamember of eventstructure class that contains the data to be filled in z coordinate . If zero (default), only one/two dimensional histogram will be used.

const char* condition	Name of the registered condition to be tested before histogram can be filled.. May contain full pathname relative to the conditions folder, separated by slash "/". If zero, no condition is tested, histo is always filled.
const char* cevx	Name of the registered eventstructure object that contains the data to be tested in condition as x coordinate.
const char* cmemx	Name of the datamember of eventstructure class that contains the data to be tested in condition as x coordinate.
const char* cevy	Name of the registered eventstructure object that contains the data to be tested in condition as y coordinate. If zero (default), only one dimensional condition will be used.
const char* cmemy	Name of the datamember of eventstructure class that contains the data to be tested in condition as y coordinate . If zero (default), only one dimensional condition will be used.

Return value:

Bool_t: Is kTRUE if adding new entry was successful. If dynamic entry of same name already existed, new entry is not added and kFALSE is returned.

Visibility:

public

Example of usage:

```
TH1D* histo1= new TH1D("spectrum1","ADC1",0,2000,2000);
AddHistogram(histo1,kTRUE,"Gamma");
TGo4WinCond* cond= new TGo4WinCond("window1","ADC1",200, 800);
AddAnalysisCondition(cond);
AddDynamicHistogram("dynamicentry1",
"spectrum1", "EuroballRawEvent","fiA1",0,0,0,0,
"window1","EuroballCalibratedEvent","fdT1Anode1");
// Connect registered histogram and condition
// fill histogram with member fiA1 from rawevent under
// window condition tested against member fiT2 from calievent
```

AddHistogram(TH1* his, const char* subfolder, Bool_t replace):

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Register a histogram to the Go4 framework. The histogram will be visible in the Go4GUI after this call, i.e. it can be monitored and copied to the GUI view panel. Go4 adopts the histogram, so the user must not delete the histogram object in the destructor. Registered histograms are placed in the TFolder Go4/Histograms which is also saved in the Go4 autosave-file when the analysis is closed, or when [AutoSave\(\)](#) is called. Optionally, a subfolder of Go4/Histograms may be specified where the histogram shall be located. Use [RemoveHistogram\(\)](#) to unregister and delete object again. **Note1: Histogram names are unique within Go4, i.e. there must not be two histograms with the same name, even in different subfolders! This is important for the TTree::Draw() feature of the dynamic list.**

Arguments:

TH1* his Pointer to histogram that shall be registered. Histogram is adopted by Go4.
const char* subfolder Name of the subfolder of Go4/Histograms where histogram shall be placed. If not specified (default), histogram will be put directly under Go4/Histograms.

Bool_t replace	If kTRUE, the new histogram his will replace any histogram of the same name that might be registered before in the same folder, and any histogram of that name that might exist in <i>any</i> subfolder (unique histogram names) The previous histogram is deleted then. If kFALSE, the new histogram will not be registered and the old histogram remains. Default is kTRUE.
Return value:	
Bool_t:	kTRUE if his was registered. Otherwise (histogram of same name already existed), kFALSE is returned.
Visibility:	
public	
Example of usage:	
<pre>TH1D* histol= new TH1D("spectrum1", "ADC1", 0, 2000, 2000); AddHistogram(histol, kTRUE, "Gamma");</pre>	

AddObject(TNamed ob, const char* subfolder, Bool_t replace):*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Register any named object to the Go4 framework. The object will be visible in the Go4GUI after this call, i.e. it can be monitored and copied to the GUI view panel. Unspecified registered objects are placed in the TFolder Go4/UserObjects which is also saved in the Go4 autosave-file when the analysis is closed, or when [AutoSave\(\)](#) is called. Optionally, a subfolder of Go4/UserObjects may be specified where the object shall be located.

Arguments:

TNamed* ob	Pointer to object that shall be registered.
const char* subfolder	Name of the subfolder of Go4/UserObjects where histogram shall be placed. If not specified (default), object will be put directly under Go4/UserObjects.
Bool_t replace	If kTRUE, the new object ob will replace any object of the same name that might be registered before in the same folder. The previous object is deleted. If kFALSE, the new object will not be registered in that case, and the old object remains. Default is kTRUE. Note that this argument is available in TGo4Analysis class only.

Return value:

Bool_t: kTRUE if ob was registered. Otherwise (object of same name already existed in UserObjects), kFALSE is returned.

Visibility:

public

Example of usage:

```
TF1* func= new TF1("Fit1", "gaus(0)*expo(3)", 0, 2000);
AddObject(func);
```

AddParameter (TGo4Parameter par, const char* subfolder):*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Register a parameter object to the Go4 framework. The parameter will be visible in the Go4GUI after this call, i.e. it can be edited at the GUI view panel. Go4 adopts the parameter, so the user must not delete the parameter object in the destructor. Registered parameters are placed in the TFolder Go4/Parameters which is also saved in the Go4 autosave-file when the analysis is closed, or when [AutoSave\(\)](#) is called. Optionally, a subfolder of Go4/Parameters may be specified where the parameter shall be located. Use [RemoveParameter\(\)](#) to unregister and delete object again.

Arguments:

TGo4Parameter* par	Pointer to parameter that shall be registered. Parameter is adopted by Go4.
const char* subfolder	Name of the subfolder of Go4/Parameters where parameter shall be placed. If not specified (default), parameter will be put directly under Go4/Parameters.

Return value:

Bool_t:	kTRUE if par was registered. Otherwise (parameter of same name already existed), kFALSE is returned.
---------	--

Visibility:

public

Example of usage:

```
TGo4Parameter* par= new TUserParameter("userdataset");  
AddParameter(par);
```

AddPicture (TGo4Picture pic, const char* subfolder):*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Register Go4 picture object to the Go4 framework. The picture will be visible in the Go4GUI after this call, i.e. it can be edited at the GUI view panel. Go4 adopts the picture, so the user must not delete the picture object in the destructor! Registered pictures are placed in the TFolder Go4/Pictures which is also saved in the Go4 autosave-file when the analysis is closed, or when [AutoSave\(\)](#) is called. Optionally, a subfolder of Go4/Pictures may be specified where the parameter shall be located. Use [RemoveParameter\(\)](#) to unregister and delete object again.

Arguments:

TGo4Picture* pic	Pointer to picture that shall be registered. Picture is adopted by Go4.
const char* subfolder	Name of the subfolder of Go4/Pictures where picture shall be placed. If not specified (default), picture will be put directly under Go4/Pictures.

Return value:

Bool_t: kTRUE if pic was registered. Otherwise (picture of same name already existed), kFALSE is returned.

Visibility:

public

Example of usage:

```
TGo4Picture* pic= new TGo4Picture("picture1","tofs"); AddPicture(pic);
```

AddTree(TTree* mytree, const char* subfolder)

Classes: TGo4Analysis

Description:

Register a root TTree to the Go4 framework. The tree will be visible in the Go4GUI after this call, i.e. the remote tree-viewing feature can be used. Tree reference is put into folder Go4/Trees. Optionally, a subfolder name may be given where the tree reference shall be located.

Note 1: A registered tree will not be saved by the Go4! This method is meant to browse trees of external analysis frameworks for online monitoring.

Note 2: The trees of the Go4 framework storage classes (TGo4FileStore, TGo4BackStore) are registered automatically, so it is not necessary to apply this method for them.

Arguments:

TTree* mytree Pointer to external tree to be registered.

const char* subfolder Name of the subfolder of Go4/Trees where reference shall be placed. If not specified (default), tree will be put directly under Go4/Trees.

Return value:

Bool_t: kTRUE if tree was registered. Otherwise (tree of same name already existed), kFALSE is returned.

Visibility:

public

Example of usage:

```
TTree* htree= new TTree("h","externaltree");  
AddTree(htree);
```

```

AddTreeHistogram(  const char* hisname,
                   const char*   treename,
                   const char*   varexp
                   TCut           selection );

```

Classes: TGo4Analysis

Description:

Add Dynamic list entry which connects a histogram to a tree. If Histogram of hisname already exists, this histogram will be taken as target for a frequent *TTree::Draw* operation. If not, the histogram will be created on first *TTree::Draw*. Strings varexp and selection are used for applying cuts and variables in the *TTree::Draw* (see ROOT Users Guide). The newly created histogram is registered automatically to the Go4, i.e. it can be monitored and copied to the GUI view panel from the folder Go4/Histograms. The frequency of this *TTree::Draw* (number of events *n* in between two fills of the histogram) can be adjusted for all tree histograms by method [SetDynlistInterval\(Int_t n\)](#).

Arguments:

const char* hisname	Name of the target histogram where the result of the <i>TTree::Draw()</i> is filled. On first execution of tree operation, this histogram is searched under the registered Go4 histograms. If not found, ROOT will create a new histogram of that name with automatic range and binsize selection and fill into this histogram. Go4 will register the newly created histogram then.
const char* treename	Name of the tree that contains the event data for the <i>TTree::Draw()</i> . On first execution of tree operation, pointer to this tree is searched under the registered Go4 TTrees. This pointer is newly initialized on every initialization of analysis.
const char* varexp	Expression for the <i>TTree::Draw()</i> specifying the leafnames to be processed. See ROOT UsersGuide for all possibilities.
TCut selection	ROOT cut object that contains a condition for the histogram filling as a text string. See ROOT UsersGuide. Note that this is not a graphical cut object TCutG!

Return value:

Bool_t:	Is kTRUE if adding new entry was successful. If dynamic entry of same name already existed, new entry is not added and kFALSE is returned.
---------	--

Visibility:

public

Example of usage:

```

// with predefined histogram spectrum1:
TH1D* histo1= new TH1D("spectrum1","ADC1",0,2000,2000);
AddHistogram(histo1,kTRUE,"Gamma");
AddTreeHistogram("spectrum1","UnpackxTree","fADC[1]",0);
// with automatically created histogram mynewhistogram and cut:
TCut window1("fQtot>560");
AddTreeHistogram("mynewhistogram","CalibratexTree","fQ1",window1);

```

AutoSave():

Classes: TGo4Analysis

Description:

Explicitly write all objects in the Go4 folders to the current autosave file. Additionally, the TGo4Calibration objects of all analysis steps are stored into the event stores of each step, if existing. This method can be generally disabled by calling [*SetAutoSave\(kFALSE\)*](#).

Arguments:

none

Return value:

void

Visibility:

public

Example of usage:

```
AutoSave() ;
```

ClearObjects(const char name)*:

Classes: TGo4Analysis

Description:

Clear (reset) objects matching the given name. Method looks for folder of name first and clears all objects contained. TH1 contents, e.g. are reset to zero, TGraph points are deleted. For parameters, the *Clear()* method is called and may be user-implemented. Note that objects and contents of complete folders can be protected against clear by method [*ProtectObjects\(\)*](#).

Arguments:

const char* name	Name of the object to be cleared, or name of object folder. If folder of that name exists in the Go4, all objects under this folder are cleared/ reset at once. If no such folder, object of name is searched in all folders and cleared.
------------------	---

Return value:

Bool_t	Is kTRUE if clear was successful. Otherwise (objects not found, or clear protected), kFALSE is returned.
--------	--

Visibility:

public

Example of usage:

```
ClearObjects("Histograms") ;
```

CloseAnalysis():

Classes: TGo4Analysis

Description:

Closes the analysis framework. Deletes event objects (event structures, io-classes, eventprocessors) that were initialized before and closes all IO. Event objects are unregistered from Go4 folder structure.. This method is typically called from the user analysis executable in batch mode. In Gui mode, pressing the “Submit” button will execute this function before initializing the new setup. Note that this method is virtual, i.e. the user analysis class may redefine what happens on closing. So it would be possible to close an external analysis framework here. Complementary function is [InitEventClasses\(\)](#).

Arguments:

none

Return value:

virtual void

Visibility:

public

Example of usage:

```
TGo4Analysis* myanalysis =new TUserAnalysis();  
myanalysis->InitEventClasses();  
myanalysis->RunImplicitLoop(2000);  
myanalysis->CloseAnalysis();
```

DeleteObjects(const char name):*

Classes: TGo4Analysis

Description:

Delete object of name, or all objects in folder name, respectively. Objects are only deleted if delete protection is not set. Usually, objects registered from user code are delete protected by default. Objects created dynamically from gui are not delete protected. . Note that objects and contents of complete folders can be protected agains deletion by method [ProtectObjects\(\)](#).

Arguments:

const char* name	Name of the object to be deleted, or name of object folder. If folder of that name exists in the Go4, all objects under this folder are deleted at once. If no such folder, object of name is searched in all folders and deleted.
------------------	--

Return value:

Bool_t	Is Is kTRUE if delete was successful. Otherwise (objects not found, or delete protected), kFALSE is returned.
--------	---

Visibility:

public

Example of usage:`DeleteObjects("Histograms");`***ExecuteLine(const char* name, Int_t* errcode=0)*****Classes:** TGo4Analysis, TGo4EventProcessor**Description:**

Process ROOT command line. Optionally provide pyroot binding: a leading '\$' will try to load and execute python script.

Arguments:

const char* name	ROOT interpreter command string.
Int_t* errcode	optional ROOT interpreter error code

Return value:

Long_t: result of ROOT interpreter execution

Visibility:

public

Example of usage:

`ExecuteLine(".x myintegrator.C");`***ExecutePython(const char* name, Int_t* errcode=0)*****Classes:** TGo4Analysis, TGo4EventProcessor**Description:**

Executes Python script in ROOT interpreter. Will bind TGo4Analysis object to python go4 Symbol

Arguments:

const char* name	ROOT interpreter command string.
Int_t* errcode	optional ROOT interpreter error code

Return value:

Long_t: result of ROOT interpreter execution

Visibility:

public

```
Example of usage:  
ExecutePython("myfit.py");
```

ExecuteScript(const char name)*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Executes ROOT Script. Note that Python is not supported in this method!

Arguments:

const char* name name of ROOT script to be executed .

Return value:

Long_t: result of script execution, or -1 if script was not found.

Visibility:

public

Example of usage:

```
if(ExecuteScript("myintegrator.C")==-1) cout << "script not found" <<endl;
```

Export(TObject ob, Go4Export_t filter)*

Classes: TGo4ExportManager

Description:

Convert and save object ob into different file formats specified by filter keynumber. Object may be collection of subobjects. Each subobject is written into single file then, conserving the hierarchy in subdirectories. In case of ROOT format, all objects will be in one output file.

Arguments:

TObject* ob Object to be exported. Currently supported are TH1*, TGraph*, TFolder*, TDirectory*, and TCollection*. If ob is a collection, folder, or directory, it is scanned recursively and all objects contained are exported, if possible. Sub-hierarchy of folders and directories are expressed as subdirectories in output file system.

Go4Export_t Keynumber for the export filter: Currently available:
GO4EX_ASCII : Plain text format for histogram (*.hdat) and TGraph (*.gdat). One line per bin/point, columns for x,y,z,counts; or point,x,y; respectively.
GO4EX_RADWARE : Radware/gf3 format. One dimensional TH1 only!
GO4EX_ROOT : Write object into one ROOT file. Filename to be specified with method TGo4ExportManager::SetOutFile(char*).

Return value:

void

Visibility:

public

Example of usage:

```
TGo4ExportManager exman("myexportfilter");
TFile* myfile=new TFile("go4autosave.root","READ");
exman.Export(myfile,GO4EX ASCII); // convert all objects of root file
                                   // into ASCII files
```

GetAnalysisCondition(const char* name)**Classes:** TGo4Analysis, TGo4EventProcessor**Description:**

Access a registered condition by name.

Arguments:

const char* name	ROOT name of the condition to be retrieved. The subfolder name under which the condition was registered may proceed condition name, separated by a slash "/".
------------------	---

Return value:

TGo4Condition*: Pointer to condition. NULL if not found.

Visibility:

public

Example of usage:

```
TGo4Condition* con= GetAnalysisCondition("Gamma/window1");
```

GetAnalysisStep(const char* name)**Classes:** TGo4Analysis**Description:**

Access an analysis step object by name.

Arguments:

const char* name	ROOT name of the analysis step.
------------------	---------------------------------

Return value:

TGo4AnalysisStep*: Pointer to analysis step. NULL if not found. From step one can obtain the factory by TGo4StepFactory * fact = (TGo4StepFactory *)step->GetStepFactory(); This is needed in macros to define input and output event and event processor.

Visibility:

public

Example of usage:

```
TGo4AnalysisStep* first= GetAnalysisStep("Unpack");  
TGo4StepFactory * fact = (TGo4StepFactory *)first->GetStepFactory();
```

GetCanvas(const char* name)

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Access a registered TCanvas by name.

Arguments:

const char* name ROOT name of the canvas object to be retrieved. The subfolder name under which the canvas was registered may proceed canvas name, separated by a slash "*/*"

Return value:

TCanvas*: Pointer to canvas. NULL if not found.

Visibility:

public

Example of usage:

```
TCanvas* c= GetCanvas("positions");
```

GetEventStructure(const char* name):

Classes: TGo4Analysis

Description:

Access to registered eventstructure object by TGo4EventElement name. Input and output events of the analysis steps are registered automatically. Note that name does not indicate the analysis stepname here, but the root name of the event itself.

Arguments:

const char* name: Name of the event object in the folder Go4/Eventobjects/Eventstructure.

Return value:

TGo4EventElement*: Pointer to event object. NULL if event of name was not found.

Visibility:

public:

Example of usage:

```
TGo4EventElement* eve= GetEventStructure("EuroballRawEvent");  
TEbEvent* useve= dynamic_cast<TEbEvent*>(eve);  
                // cast to access special event structure
```

GetHistogram(const char* name)

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Access a registered histogram by name.

Arguments:

const char* name ROOT name of the histogram to be retrieved. The subfolder name under which the histogram was registered may proceed histogram name, separated by a slash "/"

Return value:

TH1*: Pointer to histogram. NULL if not found.

Visibility:

public

Example of usage:

```
TH1D* histo1= (TH1D*) GetHistogram("Gamma/spectrum1");  
TH2D* histo2= (TH2D*) GetHistogram("ElMap");
```

GetInputEvent(const char* stepname):

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Access to the input event object of a certain analysis step. The analysis step will be identified by the ROOT name of the step object, which is set in the TGo4AnalysisStep constructor.

Arguments:

const char* stepname: Name of the analysis step object that holds the input event.

Return value:

TGo4EventElement*: Pointer to input event object. NULL if step of stepname is not existing.

Visibility:

public:

Example of usage:

```
TGo4EventElement* raw= GetInputEvent("Unpack");  
TGo4MbsEvent* mbseve= dynamic_cast<TGo4MbsEvent*>(raw);  
                        // cast to access special event structure
```

GetObject(const char name, const char* topfolder)*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Access a registered object by name, starting from the folder of name topfolder. If topfolder is zero (default), object is searched in all Go4 folders. Note that TTrees and event objects are not found by this method, since these objects should not be send to the gui. To retrieve these types, use the special getter methods [GetTree\(\)](#), [GetEventStructure\(\)](#), etc.

Arguments:

const char* name	ROOT name of the object to be retrieved. The subfolder name under which the object was registered may proceed object name, separated by a slash "/"
const char* topfolder	Name of the folder under which object shall be searched. Useful if path to object is not known completely.

Return value:

TNamed*: Pointer to object. NULL if not found.

Visibility:

public

Example of usage:

```
TH1D* histo1= (TH1D*) GetObject("Histograms/Gamma/spectrum1");  
TH1D* histo2= (TH1D*) GetObject("spectrum2", "Histograms");  
TGo4WinCond* con= (TGo4WinCond*) GetObject("Conditions/Window3");
```

GetOutputEvent(const char stepname):*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Access to the output event object of a certain analysis step. The analysis step will be identified by the ROOT name of the step object, which is set in the TGo4AnalysisStep constructor.

Arguments:

const char* stepname:	Name of the analysis step object that holds the input event..
-----------------------	---

Return value:

TGo4EventElement*: Pointer to output event object. NULL if step of stepname is not existing.

Visibility:

public:

Example of usage:

```
TGo4EventElement* eve= GetOutputEvent("Unpack");
TUserEvent* useve= dynamic_cast<TUserEvent*>(eve);
                // cast to access special event structure
```

GetOutputEvent():

Classes: TGo4Analysis

Description:

Fast access to the output event object of the *most recent analysis step* that was processed before this call. If called in the [UserEventFunc\(\)](#), it yields the resulting event object of the last active step of the analysis cycle.

Arguments:

None

Return value:

TGo4EventElement*: Pointer to output event object of the last analysis step processed.

Visibility:

public:

Example of usage:

```
TGo4EventElement* eve= GetOutputEvent();
```

GetParameter(const char* name)

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Access a registered parameter by name.

Arguments:

const char* name ROOT name of the parameter object to be retrieved. The subfolder name under which the parameter was registered may proceed parameter name, separated by a slash "/"

Return value:

TGo4Parameter*: Pointer to parameter. NULL if not found.

Visibility:

public

Example of usage:

```
TGo4Parameter* par= GetParameter("RunSetup1");  
TUserParameter* upar=dynamic_cast<TUserParameter*>(par);
```

GetPicture(const char* name)

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Access a registered picture by name.

Arguments:

const char* name	ROOT name of the picture object to be retrieved. The subfolder name under which the picture was registered may proceed picture name, separated by a slash "/"
------------------	---

Return value:

TGo4Picture*:	Pointer to picture. NULL if not found.
---------------	--

Visibility:

public

Example of usage:

```
TGo4Picture* pic= GetPicture("frame3");
```

GetTree(const char* name)

Classes: TGo4Analysis

Description:

Access a registered tree by name.

Arguments:

const char* name	ROOT name of the tree to be retrieved. The subfolder name under which the tree was registered may proceed tree name, separated by a slash "/"
------------------	---

Return value:

TTree*: Pointer to tree. NULL if not found.

Visibility:

public

Example of usage:

```
TTree* mytree= GetTree("tree2");
```

InitEventClasses():

Classes: TGo4Analysis

Description:

Initialization of the analysis framework. Creates event objects (event structures, IO classes, event processors) as defined in the event factories of the analysis steps. Event objects are registered automatically in Go4 folder structure. Previous event objects are deleted and unregistered first. This method is typically called from the user analysis executable in batch mode. In Gui mode, pressing the “Submit” button will execute this function, too. Note that this method is virtual, i.e. the user analysis class may redefine what happens on initialization. So it would be possible to initialize an external analysis framework here. Complementary function is [CloseAnalysis\(\)](#), which deletes all existing event objects and closes all IO.

Arguments:

none

Return value:

virtual Bool_t Is kTRUE if init was successful.

Visibility:

public

Example of usage:

```
TGo4Analysis* myanalysis =new TUserAnalysis();  
myanalysis->InitEventClasses();  
myanalysis->RunImplicitLoop(2000);
```

TGo4Analysis::Instance():

Classes: available everywhere when linked against libGo4Analysis.so

Description:

Static Method. Get the pointer to the current analysis framework singleton. This reference can be used to invoke any public method of the class TGo4Analysis from outside the class. This is e.g. meaningful if framework settings shall be changed from within the event processor. Note that a “dummy” analysis framework will be created if this method is called without having created the user analysis object before!

Arguments:

none

Return value:

TGo4Analysis* Pointer to analysis framework singleton.

Visibility:

public

Example of usage:

```
TGo4Analysis::Instance()->SetAutoSaveFile("StageTwo.root");
```

IsAutoSaveOn():

Classes: TGo4Analysis

Description:

Check if autosaving is enabled.

Arguments:

none

Return value:

Bool_t Is kTRUE if autosave file is enabled for read and write.

Visibility:

public

Example of usage:

```
if(IsAutoSaveOn())  
    cout <<"Autosaving is enabled" << endl;;
```

IsAutoSaveFileChange():

Classes: TGo4Analysis

Description:

Check if analysis runs with automatic autosave filename change. In this case, for each new *.lmd file of an input file list, a new autosave file will be created with a name derived from the current input file name. Set this property with [SetAutoSaveFileChange\(\)](#).

Arguments:

none

Return value:

Bool_t Is kTRUE if running in file change mode.

Visibility:

public

Example of usage:

```
if(IsAutoSaveFileChange())  
    cout <<"analysis with autosave filechange mode" << endl;
```

IsBatchMode():**Classes:** TGo4Analysis**Description:**

Check if analysis was invoked in batch mode (without GUI).

Arguments:

none

Return value:

Bool_t Is kTRUE if running in batch mode.

Visibility:

public

Example of usage:

```
TGo4Analysis* myanalysis =new TUserAnalysis();  
// .. do setup, init etc.  
if(myanalysis->IsBatchMode())  
    cout <<" Starting in batch mode" << endl;
```

IsClientMode():**Classes:** TGo4Analysis**Description:**

Check if analysis was invoked in client mode (controlled by Go4 GUI).

Arguments:

none

Return value:

Bool_t Is kTRUE if running in client mode.

Visibility:

public

Example of usage:

```
TGo4Analysis* myanalysis =new TUserAnalysis();
```

```
// .. do setup, init etc.
if(myanalysis->IsClientMode())
    cout <<" Starting in client mode" << endl;
```

IsInitDone():

Classes: TGo4Analysis

Description:

Check if initialization of analysis was done correctly.

Arguments:

none

Return value:

Bool_t Is kTRUE if init was successful.

Visibility:

public

Example of usage:

```
TGo4Analysis* myanalysis =new TUserAnalysis();
// .. do setup, init etc.
if(myanalysis->IsInitDone())
    myanalysis->RunImplicitLoop(2000);
else
    cerr <<" Error on init" << endl;
```

IsKeepInputEvent ():

Classes: TGo4EventProcessor

Description:

Test if current input event of this processor's analysis step is to be used again in the next analysis cycle, without invoking the Clear() and Fill() methods which would erase the previous contents. This is the case when a "1 to n" event building functionality has been set by function [SetKeepInputEvent\(Bool_t\)](#). Checking the state of the input event is especially necessary for composite event building, i.e. a Go4 composite event is processed by several sub-processors. Here each sub-processor needs to be aware if the common input event might have been set into the "keep mode" by another sub-processor, so the own processing of a subcomponent might have to cease until the next new event is coming.

Arguments:

none

Return value:

public

Example of usage:

```
if(IsNewInputFile()){  
    ShowEvent("Unpack",false); // print first event  
    SetNewInputFile(false); // reset flag  
}
```

IsRunning():

Classes: TGo4Analysis

Description:

Check if analysis slave is in “running”state. To be used from ROOT macro running in Go4 CintServer environment to check the state set via the start/stop buttons of controlling GUI. Running state may be changed by method [SetRunning\(Bool_t\)](#), too.

Arguments:

none

Return value:

Bool_t Is kTRUE if analysis slave is running, otherwise kFALSE..

Visibility:

public

Example of usage:

```
while(myanalysis->IsRunning()){  
    ...; //user actions independent of go4 eventloop here...  
}
```

IsServerMode():

Classes: TGo4Analysis

Description:

Check if analysis was invoked in analysis server mode (to be observed by GUIs).

Arguments:

none

Return value:

Bool_t Is kTRUE if running in server mode.

Visibility:

public

Example of usage:

```
TGo4Analysis* myanalysis =new TUserAnalysis();  
// .. do setup, init etc.  
if(myanalysis->IsServerMode())  
    cout <<" Starting in server mode" << endl;
```

LoadObjects (const char* filename):**Classes:** TGo4Analysis**Description:**

Load objects from a Go4 autosave file back into the Go4 object manager memory. Usually, this is done automatically on submitting Go4 settings if autosave is enabled. However, one might exchange parameters or conditions on the fly by this method. Note that already existing histograms in memory are not overwritten by histograms from file of the same name. This method will change the general autosave filename which is used for next AutoSave()!

Arguments:

const char* filename	Name of autosave file to load. If 0, objects are loaded from most recent autosave filename, or from filename as specified in the Go4 analysis setup.
----------------------	--

Return value:

Bool_t:	kTRUE if loading was successful. kFALSE if file could not be opened.
---------	--

Visibility:

public

Example of usage:

```
LoadObjects("run123.root");
```

LoadStatus (const char* filename):**Classes:** TGo4Analysis**Description:**

Load analysis settings (parameters for event factory, filenames) from file and apply them to the analysis. On calling this method, a [CloseAnalysis\(\)](#) will be executed before setting the new parameters, i.e. all event objects of the previous analysis setup are deleted and all files are closed. Status file can be saved using the [SaveStatus\(\)](#) method.

Arguments:

const char* filename	Name of preferences file. If no filename is specified, file Go4AnalysisPrefs.root will be used.
----------------------	---

Return value:

Bool_t:	kTRUE if loading was successful. kFALSE if file could not be opened.
---------	--

Visibility:

public

Example of usage:

```
LoadStatus("OnlinePrefs.root");
```

TGo4Log::LogfileEnable (Bool_t on):**Classes:** TGo4Log (available everywhere)**Description:**

Switch on or off the logfile output. The global ignore level of go4 as set with [TGo4Log::SetIgnoreLevel\(\)](#) defines what kind of messages are logged. Logfile can be opened user-defined by calling `TGo4Log::OpenLogfile`. By default, go4 will open the logfile "*go4logfile.txt*" in a non-append mode.

Arguments:

Bool_t on	If kTRUE, all go4 messages output will be written to current logfile. Otherwise, nothing is written to file.
-----------	--

Return value:

void

Visibility:

static public

Example of usage:

```
TGo4Log::LogfileEnable(kTRUE);
```

TGo4Log::Message (Int_t prio, const char* text,...):**Classes:** TGo4Log (available everywhere)**Description:**

Printout message text on the local terminal and/or write it to the logfile. Priority prio defines type of message and action. Messages with priority less than the global ignore level ([TGo4Log::SetIgnoreLevel](#)) are suppressed in printout and logfile. Supports variable argument list for format strings in the text, just like in C printf() function.

Note: It is recommended to use [TGo4Analysis::Message](#) instead of this method, since it provides the same printout and logging functionality, but adds the feature to display the message in the gui log window.

Arguments:

Int_t prio	Priority of message that defines output mode:
0:	Debug or go4 kernel information
1:	Informational message
2:	Warning message
3:	Error message

const char* text	Text to be displayed in the message. May contain printf() format strings which define the output of the variable argument list at the end.
...	Variable argument list like in printf(). Any number of arguments of any type should be supported here. Uses internally the va_list structure of <stdarg>.

Return value:
void

Visibility:
static public

Example of usage:
TGo4Log::Message(2, "Found event with id %d from input %s", evid, filename);

TGo4Log::OpenLogfile (const char* filename, const char* headercomment, Bool_t appendmode):

Classes: TGo4Log (available everywhere)

Description:
Set name of logfile for Go4 messages. File will be opened with name filename. Optionally, the text of a comment may be specified that appears in the first line of the logfile. If appendmode is kTRUE, the output is added to previous file of same filename, otherwise the old filename is overwritten. Any previous logfile, if existing, will be closed by this method. Whether anything is written to file is controlled by the function [TGo4Log::LogfileEnable\(\)](#). The global ignore level of go4 as set with [TGo4Log::SetIgnoreLevel\(\)](#) defines what kind of messages are displayed or logged. Without calling this function, go4 will open by default a logfile "go4logfile.txt" in a non-append mode.

Arguments:

const char* filename	Name of logfile. If filename is NULL, go4 will open file <i>go4log-123456.txt</i> , with the current pid "123456" as part of the name.
const char* headercomment	Optional text comment to be added at the beginning of the logfile. May contain formatting characters like "\n" or "\t".
Bool_t appendmode	If kTRUE, all following output will be appended to file of filename if existing. Otherwise, content of previous file is overwritten. Default is non-append.

Return value:
void

Visibility:
static public

Return value:

void

Visibility:

static public

Example of usage:

```
TGo4Log::SetIgnoreLevel(0); // get full debug infos
```

```

MakeBoxCond(const char* fullname,
            Double_t cx,
            Double_t cy,
            Double_t a1,
            Double_t a2,
            Double_t theta,
            const char* HistoName) :

```

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access a shaped polygon condition object by name in the analysis *Conditions* folder. The initial shape type is defined as rectangular box with parameters as specified, but may be altered by condition editor during runtime. If a shaped condition of same name already exists (read from autosave file), it will just be returned. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing condition from autosave file here.

Arguments:

const char* fullname	Condition name (optionally with subfolder name)
Double_t cx	Center coordinate of box shape along x axis
Double_t cy	Center coordinate of box shape along y axis
Double_t a1	Extension (half width) of box shape along first side
Double_t a2	Extension (half width) of box shape along second side
Double_t theta	Tilt angle in degrees between first box side a1 and x axis
const char* HistoName	Optional: Name of histogram to which condition is assigned.

Return value:

TGo4ShapedCond*

Visibility:

public

Example of usage:

```
TGo4ShapedCond* cond = MakeBoxCond("Folder/Mybox", 200, 300, 40, 60, 45);
```

```
MakeCircleCond(const char* fullname,
               Int_t npoints,
               Double_t cx,
               Double_t cy,
               Double_t r,
               const char* HistoName) :
```

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access a shaped polygon condition object by name in the analysis *Conditions* folder. The initial shape type is defined as circle with parameters as specified, but may be altered by condition editor during runtime. If a shaped condition of same name already exists (read from autosave file), it will just be returned. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing condition from autosave file here.

Arguments:

const char* fullname	Condition name (optionally with subfolder name)
Int_t npoints	Number of points in shaped condition
Double_t cx	Center coordinate of circle along x axis
Double_t cy	Center coordinate of circle along y axis
Double_t r	Radius of circle
const char* HistoName	Optional: Name of histogram to which condition is assigned.

Return value:

TGo4ShapedCond*

Visibility:

public

Example of usage:

```
TGo4ShapedCond* cond = MakeCircleCond("Folder/MyCircle",
100, 3, 4, 5, "maphistogram");
```

```

MakeEllipseCond(const char* fullname,
                Int_t npoints,
                Double_t cx,
                Double_t cy,
                Double_t a1,
                Double_t a2,
                Double_t theta,
                const char* HistoName) :

```

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access a shaped polygon condition object by name in the analysis *Conditions* folder. The initial shape type is defined as ellipse with parameters as specified, but may be altered by condition editor during runtime. If a shaped condition of same name already exists (read from autosave file), it will just be returned. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing condition from autosave file here.

Arguments:

const char* fullname	Condition name (optionally with subfolder name)
Int_t npoints	Number of points in shaped condition
Double_t cx	Center coordinate of ellipse along x axis
Double_t cy	Center coordinate of ellipse along y axis
Double_t a1	First half axis extension of ellipse
Double_t a2	Second half axis extension of ellipse
Double_t theta	Tilt angle in degrees between first half axis a1 and x axis
const char* HistoName	Optional: Name of histogram to which condition is assigned.

Return value:

TGo4ShapedCond*

Visibility:

public

Example of usage:

```

TGo4ShapedCond* cond = MakeEllipseCond("Folder/MyEllipse", 60, -
500.3, 300.5, 20, 40, 45, "Emaphistogram");

```

MakeParameter(const char fullname,
const char* classname,
const char* newcmd):*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access a parameter object by name in the analysis parameter folder. If a TGo4Parameter of same name already exists (read from autosave file), it will just be returned. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing parameter from autosave file here.

Arguments:

const char* fullname	Parameter name (optionally with subfolder name)
const char* classname	Name of required parameter class, it should be known to ROOT
const char* newcmd	Optional command string to instantiate the parameter e.g. "new UserParameter(%s, 1000, 2000)", where %s is place for parameter name. To be specified if parameter constructor needs more arguments than the parameter name. Or: macro name to set parameter value. Macro is executed immediately after parameter creation (or loading from autosave file) and thus overwrites parameters value. The macro name should start with "set_" like "set_RocPar.C"

Return value:

TGo4Parameter*

Visibility:

public

Example of usage:

```
fCalipar =  
(TXXCalibPar*) MakeParameter("CaliPar", "TXXCalibPar", "set_Cal33.C");
```

```
MakePolyCond(const char* fullname,
              Int_t npoints,
              Double_t (*points) [2],
              const char* HistoName,
              Bool_t shapedcond) :
```

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access a polygon condition object by name in the analysis *Conditions* folder. If a polygon condition of same name already exists (read from autosave file), it will just be returned. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing condition from autosave file here.

Arguments:

const char* fullname	Condition name (optionally with subfolder name)
Int_t npoints	Number of points in polygon condition
Double_t (* points) [2]	Array of polygon point coordinates.
const char* HistoName	Optional: Name of histogram to which condition is assigned.
Bool_t shapedcond	Optional: if true, create polygon condition as TGo4ShapedCond (may be parametrized as circular/elliptic/rectangular shape later)

Return value:

TGo4PolyCond*

Visibility:

public

Example of usage:

```
Double_t points[4][2] = { {10, 0}, {10, 10}, {5, 15}, {5, 5} };
TGo4PolyCond* cond = MakePolyCond("Folder/CondName", 4, points);
```


*MakeTH1 (char type,
const char* fullname, const char* title,
Int_t nbinsx, Double_t xlow, Double_t xup,
const char* xtitle, const char* ytitle) :*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access one dimensional histogram of specified type and name in the analysis *Histogram* folder. If a histogram of exactly the same name and type already exists (read from autosave file), it will just be returned.. If a histogram of same name, but of different type already exists, it will be converted to a histogram of the new type before returning the pointer. In any case histogram and axis titles are reset to the values as specified in the title, xtitle, and ytitle arguments. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing histogram from autosave file here.

Arguments:

char type	Histogram type to create: T, 'i' for TH1I - Int_t as bin content (default) F, 'f' for TH1F - Float_t as bin content D, 'd' for TH1D - Double_t as bin content S, 's' for TH1S - Short_t as bin content C, 'c' for TH1C - Char_t as bin content
const char* fullname	Histogram name (optionally with subfolder name)
const char* title	Histogram title
Int_t nbinsx	Number of bins for x axis
Int_t xlow	Lower value of x axis range
Int_t xup	Upper value of x axis range
const char* xtitle	Optional title for X axis of histogram.
const char* ytitle	Optional title for Y axis of histogram.

Return value:

TH1*

Visibility:

public

Example of usage:

fHis1 = MakeTH1('I', "His1","Condition histogram", 5000, 1., 5001.);

```

MakeTH2 ( char type,
           const char* fullname, const char* title,
           Int_t nbinsx, Double_t xlow, Double_t xup,
           Int_t nbinsy, Double_t ylow, Double_t yup,
           const char* xtitle, const char* ytitle, const char* ztitle ) :

```

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access two dimensional histogram of specified type and name in the analysis *Histogram* folder. If a histogram of exactly the same name and type already exists (read from autosave file), it will just be returned.. If a histogram of same name, but of different type already exists, it will be converted to a histogram of the new type before returning the pointer. In any case histogram and axis titles are reset to the values as specified in the title, xtitle, ytitle, and ztitle arguments. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing histogram from autosave file here.

Arguments:

char type	Histogram type to create: 'I', 'i' for TH2I - Int_t as bin content (default) 'F', 'f' for TH2F - Float_t as bin content 'D', 'd' for TH2D - Double_t as bin content 'S', 's' for TH2S - Short_t as bin content 'C', 'c' for TH2C - Char_t as bin content
const char* fullname	Histogram name (optionally with subfolder name)
const char* title	Histogram title
Int_t nbinsx	Number of bins for x axis
Int_t xlow	Lower value of x axis range
Int_t xup	upper value of x axis range
Int_t nbinsy	Number of bins for y axis
Int_t ylow	Lower value of y axis range
Int_t yup	Upper value of y axis range
const char* xtitle	Optional title for X axis of histogram.
const char* ytitle	Optional title for Y axis of histogram.
const char* ztitle	Optional title for Z axis of histogram. .

Return value:

TH2*

Visibility:

public

Example of usage:

```

fCr1Ch1x2 = MakeTH2('I', "Cr1Ch1x2", "Crate 1 channel 1x2",
                   200, 1., 5001., 200, 1., 5001.);

```

```
MakeWinCond( const char* fullname,  
             Double_t xmin, Double_t xmax,  
             const char* HistoName ) :
```

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access a one dimensional window condition by name in the analysis *Conditions* folder. If a window condition of same name already exists (read from autosave file), it will just be returned. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing condition from autosave file here.

Arguments:

const char* fullname	Condition name (optionally with subfolder name)
Double_t xmin	Condition window lower edge
Double_t xmax	Condition window upper edge
const char* HistoName	Optional: Name of histogram to which condition is assigned.

Return value:

TGo4WinCond*

Visibility:

public

Example of usage:

```
TGo4WinCond* conny1 = MakeWinCond("condition1", 100, 2000, "His1");
```

```
MakeWinCond( const char* fullname,  
             Double_t xmin, Double_t xmax,  
             Double_t ymin, Double_t ymax,  
             const char* HistoName ) :
```

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Create or access a two dimensional window condition by name in the analysis *Conditions* folder. If a window condition of same name already exists (read from autosave file), it will just be returned. With method [SetMakeWithAutosave\(kFALSE\)](#) one can globally exclude to use an already existing condition from autosave file here.

Arguments:

const char* fullname	Condition name (optionally with subfolder name)
Double_t xmin	Condition window X value lower edge
Double_t xmax	Condition window X value upper edge
Double_t ymin	Condition window Y value lower edge
Double_t ymax	Condition window Y value upper edge
const char* HistoName	Optional: Name of histogram to which condition is assigned.

Return value:

TGo4WinCond*

Visibility:

public

Example of usage:

```
TGo4WinCond* conny2 = MakeWinCond("condition2", 100, 2000, 300, 400, "maphis");
```

Message (Int_t prio, const char* text,...):**Classes:** TGo4Analysis, TGo4EventProcessor**Description:**

Send a text message to the gui log window, and/or printout message text on the local terminal. Priority prio defines type of message and action. Supports variable argument list for format strings in the text, just like in C printf() function. If logfile is open and enabled, message is written to logfile.

Arguments:

Int_t prio	Priority of message that defines output mode: 0: Printout on local terminal only if debug level is enabled (with TGo4Log::SetIgnoreLevel(0)) <0: Printout on local terminal anyway, independent of ignore level 1: Informational message on gui log window and printout 2: Warning message on gui log window and printout 3: Error message on gui log window and printout
const char* text	Text to be displayed in the message. May contain printf() format strings which define the output of the variable argument list at the end.


```
NewStepSource ( const char* name,  
                TGo4EventSourceParameter* par );
```

Classes: TGo4Analysis

Description:

Closes down event source implementation of analysis step and create new event source for this step as specified by parameter par. May be used to switch input on the fly without initializing the complete analysis. One output file e.g. can be filled from several input files in a loop; if one input file ends, the next will be set as source

Arguments:

*const char** *name* Name of the analysis step.
*TGo4EventSourceParameter** *par* Eventsource parameter that defines the new event source.

Return value:

Bool_t: kTRUE if analysis step of name was found, otherwise kFALSE.

Visibility:

public

Example of usage:

```
TGo4FileSourceParameter* fpar=  
    new TGo4FileSourceParameter ("run1.lmd");  
NewStepSource ("Unpack", fpar);
```

```
NewStepStore (const char* name,  
              TGo4EventStoreParameter* par );
```

Classes: TGo4Analysis

Description:

Closes down event store implementation of analysis step and create new event store for this step as specified by parameter par. May be used to switch output on the fly without initializing the complete analysis. One input file e.g. can be split into several output files depending on the event number.

Arguments:

*const char** *name* Name of the analysis step.
*TGo4EventStoreParameter** *par* Eventstore parameter that defines the new event store.

Return value:

Bool_t: kTRUE if analysis step of name was found, otherwise kFALSE.

Visibility:

public

Example of usage:

```
TGo4FileStoreParameter* fpar=  
    new TGo4FileStoreParameter ("output2.root");  
NewStepStore ("Unpack", fpar);
```

NextMatchingObject (const char expression,
const char* foldername,
Bool_t reset):*

Classes: TGo4Analysis

Description:

Delivers pointer to next object of the Go4 folder structure with a name matching the expression. If reset is true, the list of matching objects will be created anew by comparing all names with expression. If reset is false, the next object of a previously created matching list is returned. Optionally the search can be limited to a given folder as specified by the foldername.

Arguments:

const char* expression	Regular expression for object names
const char* foldername	Name of the object manager subfolder to scan for the matching objects. All subfolders of this folder are scanned recursively. If foldername is 0, scan is started in Go4 top folder.
Bool_t reset	If true, search list will be created by comparing all object names with expression. Otherwise, this method just returns the next object of an already created list of matches.

Return value:

TObject* :	Pointer to next matching object. If 0, end of matching list is reached, or no matching object was found.
------------	--

Visibility:

public

Example of usage:

```
TObject* result=0;  
Bool_t reset=kTRUE;  
while((result=NextMatchingObject("*Ch1*", "Histograms", reset))!=0){  
    reset=kFALSE;  
    printf("Found result object: %s\n",result->GetName());  
}
```

Print(Option_t opt):*

Classes: TGo4Analysis

Description:

Prints out the analysis configuration, including autosave file settings and set up of the analysis steps

Arguments:

Option_t* opt Option string. Not yet in use.

Return value:

void

Visibility:

public

Example of usage:

Print() ;

PrintConditions(const char expression):*

Classes: TGo4Analysis

Description:

Prints out the counter statistics of all conditions in the Go4/Conditions folder to the local analysis terminal. Subfolder names are displayed (if any). The conditions output (one line per condition) is indented depending on the subfolder level. Condition true counter is displayed as ascii bargraph showing the percentage of total calls of TGo4Condition::Test() being true.

Arguments:

const char* expression Wildcard regular expression for the condition name. Only objects matching the expression are printed. Default is "*".

Return value:

void

Visibility:

public

Example of usage:

PrintConditions("Poly*") ;

PrintDynamicList():

Classes: TGo4Analysis

Description:

Prints out the list of dynamic list entries to the analysis output terminal.

Arguments:

none

Return value:

void

Visibility:

public

Example of usage:

```
PrintDynamicList();
```

PrintHistograms(const char expression):*

Classes: TGo4Analysis

Description:

Prints out the total content of all histograms in the Go4/Histograms folder to the local analysis terminal. Subfolder names are displayed (if any). The histogram output (one line per histogram) is indented depending on the subfolder level.

Arguments:

const char* expression

Wildcard regular expression for the histogram name. Only objects matching the expression are printed. Default is "*".

Return value:

void

Visibility:

public

Example of usage:

```
PrintHistograms();
```

Process():

Classes: TGo4Analysis

Description:

Process one main cycle of Go4 eventloop from a **root macro running in the Go4CintServer** (go4root executable, or started with go4_init.C script). Will first execute any command from gui in the queue, then call MainCycle() to process analysis steps, user event function and dynamic list (if existing). **This call is required inside any explicit loop of a macro to process go4 framework analysis action.** GUI event ratemeter is also updated by this method.

Arguments:

none

Return value:

Int_t Indicates Go4 running state. Returns 0 if analysis is running, otherwise value <0. May be used to react on Stop button from GUI in user macro.

Visibility:

public

Example of usage:

```
TGo4Analysis* go4=TGo4Analysis::Instance();  
while(go4->Process()==0){ // run go4 loop until it's stopped  
; // may put additional eventwise actions here...  
}
```

ProtectObjects(const char name , const Option_t* flags):*

Classes: TGo4Analysis

Description:

Change protection properties for object of specified name. If object is a folder, change properties of all objects in this folder recursively. Flags may contain key letters like:

"+C"/"-C" to enable/disable protection against Clear() (histogram zeroing etc).

"+D"/"-D" to enable/disable protection against object deletion.

For example flags="+C-D", "+C+D", "-D-C", "-C". Properties not appearing in flags are not changed.

NOTE: Be careful when changing delete protections for objects that are created in the compiled code! By default, all objects registered from compiled code are delete protected. If protection is disabled, they might be deleted from the Go4 GUI, causing possibly invalid pointers in the analysis code!

Protection flags are conserved if objects are saved to a root file.

Arguments:

const char* name Name of the object /folder to change the protection bits.

const Option_t* flags String with specifiers how to change protections.
"+C"/"-C" to enable/disable [ClearObjects\(\)](#).
"+D"/"-D" to enable/disable [DeleteObjects\(\)](#).

Return value:

Bool_t: True if at least one object of name was found and its protection was changed.
False if no object of such name.

Visibility:

public

Example of usage:

```
ProtectObjects("Histograms", "+C");  
                                         //prevent reset for all histograms
```

RemoveAnalysisCondition(const char* name)

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Remove a registered condition from the framework. Condition will be removed from Go4 conditions folder and deleted.

Arguments:

const char* name ROOT name of the condition to be removed. The subfolder name under which the condition was registered may proceed condition name, separated by a slash
"/"

Return value:

Bool_t: kTRUE if condition was found and removed. Is kFALSE if condition of that name was not found.

Visibility:

public

Example of usage:

```
RemoveAnalysisCondition("Gamma/window1");
```

RemoveCanvas(const char name)*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Remove a registered TCanvas from the framework. Canvas will be removed from Go4/Canvases folder and deleted.

Arguments:

const char* name ROOT name of the TCanvas to be removed. The subfolder name under which the canvas was registered may proceed canvas name, separated by a slash “/”

Return value:

Bool_t: kTRUE if canvas was found and removed, kFALSE if canvas of that name was not found.

Visibility:

public

Example of usage:

```
RemoveCanvas("positions");
```

RemoveDynamicEntry(const char entryname, const char* listname)*

Classes: TGo4Analysis

Description:

Remove a dynamic entry of entryname from the dynamic list of listname. Note that objects which are referenced from dynamic entry are not deleted, since they are owned by their special folders.

Arguments:

const char* entryname ROOT name of the Go4 dynamic entry to be removed.

const char* listname ROOT name of the dynamic list containing the entry to be removed. If zero (default), entry will be removed from the currently active dynamic list.

Return value:

Bool_t: kTRUE if entry was found and removed, kFALSE if parameter of that name was not found.

Visibility:

public

Example of usage:

```
RemoveDynamicEntry("Dynamic1");
```

RemoveHistogram(const char name, Bool_t del)*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Remove a registered histogram from the framework. Histogram will be removed from Go4 histogram folder. If del is true, histogram is also deleted.

Arguments:

const char* name ROOT name of the histogram to be removed. The subfolder name under which the histogram was registered may proceed histogram name, separated by a slash “/”

Bool_t del If kTRUE (default), removed histogram is deleted by Go4. If kFALSE, the histogram will be unregistered only, without calling its destructor. Useful if a histogram was registered that is owned by an external framework. **Note: this argument is available in class TGo4Analysis only.**

Return value:

Bool_t: kTRUE if histogram was found and removed. Is kFALSE if histogram of that name was not found.

Visibility:

public

Example of usage:

```
RemoveHistogram("Gamma/spectrum1");
```

RemoveObject(const char name, Bool_t del)*

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Remove a registered object from the UserObjects folder. If del is true, objects is also deleted.

Arguments:

const char* name ROOT name of the object to be removed. The subfolder name under which the object was registered may proceed object name, separated by a slash “/”

Bool_t del If kTRUE (default), removed object is deleted by Go4. If kFALSE, the object will be unregistered only, without calling its destructor. Useful if an object was registered that is owned by an external framework. Note: this argument is available in class TGo4Analysis only.

Return value:

Bool_t: kTRUE if object was found and removed. Is kFALSE if object of that name was not found.

Visibility:

public

Example of usage:

```
RemoveObject("Graph1");
```

RemoveParameter(const char* name)

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Remove a registered parameter from the framework. Parameter will be removed from Go4/Parameters folder and deleted.

Arguments:

const char* name	ROOT name of the parameter to be removed. The subfolder name under which the parameter was registered may proceed parameter name, separated by a slash “/”
------------------	--

Return value:

Bool_t:	kTRUE if parameter was found and removed, kFALSE if parameter of that name was not found.
---------	---

Visibility:

public

Example of usage:

```
RemoveParameter("Calibration5");
```

RemovePicture(const char* name)

Classes: TGo4Analysis, TGo4EventProcessor

Description:

Remove a registered picture from the framework. Picture will be removed from Go4/Pictures folder and deleted.

Arguments:

const char* name	ROOT name of the picture to be removed. The subfolder name under which the picture was registered may proceed picture name, separated by a slash “/”
------------------	--

Return value:

Bool_t:	kTRUE if picture was found and removed, kFALSE if picture of that name was not found.
---------	---

Visibility:

public

To be called from outside analysis class only!

Example of usage:

```
TGo4Analysis* myanalysis =new TUserAnalysis();
myanalysis->InitEventClasses();
myanalysis->RunImplicitLoop(2000);
```

SaveStatus (const char* filename):**Classes:** TGo4Analysis**Description:**

Save analysis settings (parameters of analysis steps, ..) to a root file. These settings may be restored using [LoadStatus\(const char*\)](#) method.

Arguments:

const char* filename Name of preferences file. If no filename is specified, file Go4AnalysisPrefs.root will be taken.

Return value:

Bool_t: kTRUE if saving was successful. kFALSE if status object could not be created, or if file could not be opened.

Visibility:

public

Example of usage:

```
SaveStatus("OnlinePrefs.root");
```

SendObjectToGUI (TNamed* ob):**Classes:** TGo4Analysis, TGo4EventProcessor**Description:**

Send any object from the analysis to the gui via data channel. If gui is not available (batch mode), this call has no effect except for a warning message. This method can be used to send objects only if certain conditions in the analysis are true (event driven monitoring of objects). Objects that arrive on gui side unrequested appear in the local memory folder. However, one can prepare the GUI to deliver an arrived object of a certain name to a user written gui, by method *TGo4GUIRegistry::ReDirectObject()*.

Arguments:

TNamed* ob Pointer to object to be send..

Return value:

void

Visibility:

public

Example of usage:

```
TH1* his=GetHistogram("Gamma/spectrum1");
SendObjectToGUI(his);
```

SetAnalysisCondition (*const char** *name*,
*TGo4Condition** *con*,
Bool_t *counter*);

Classes: TGo4Analysis

Description:

Sets an already registered condition of name to the values of the external condition con. If condition of given name is not existing in the folder, a copy of the external condition con is registered instead of updating the old condition.

Arguments:

const char* name	Name of the registered condition under folder Go4/Conditions. Optionally, the string name may contain a subfolder name that proceeds the condition name and is separated by a slash "/". Then condition is searched in that subfolder of Go4/Conditions.
TGo4Condition* con	Pointer to external condition that contains the values for updating the registered condition. Note that this external condition is never adopted by framework! If condition of name does not exist, a new condition of the name will be created, updated from con and registered.
Bool_t counter	If kTRUE (default), the condition counter information is also updated and replaced by the counters of condition con. Otherwise, the counter settings of the condition of name are left as before, only the condition ranges are updated.

Return value:

Bool_t:	kTRUE if con was updated or registered correctly. Otherwise kFALSE is returned.
---------	---

Visibility:

public

Example of usage:

```
TGo4WinCond* cond= new TGo4WinCond("window1","ADC1",200, 800);
SetAnalysisCondition("window2",cond);
```


SetAutoSaveInterval (Int_t seconds):

Classes: TGo4Analysis

Description:

Specify the time in seconds that shall be processed in between two automatic calls of [AutoSave\(\)](#). Use method [SetAutoSaveFile\(\)](#) to specify the autosave file properties. The default autosave interval is set from static constant fgiAUTOSAVECOUNTS which is currently 500 s.

Arguments:

Int_t val Number of seconds in between two automatic saves. For seconds=0, frequent autosaving will be disabled and autosavefile will be written at the end of analysis only.

Return value:

void

Visibility:

public

Example of usage:

```
SetAutoSaveInterval(300);
```

SetDynListInterval (Int_t val):

Classes: TGo4Analysis

Description:

Specify the number of analysis cycles that shall be processed in between two *TTree::Draw()* executions on the tree histogram entries of the dynamic list. All events that were filled into the tree within this interval are used in the *TTree::Draw()*. The useful value strongly depends on the eventrate. It should be put such that it takes no longer than 10 seconds to update the histograms that shall be filled from the dynamic *TTree::Draw*. Default dynlistinterval is set from static constant fgiDYNLISTINTERVAL which is currently 1000.

Arguments:

Int_t val Number of events in between two dynamic list processings on treehistogram entries..

Return value:

void

Visibility:

public

Example of usage:

```
SetDynListInterval(200);
```

SetFirstStep (const char name):*

Classes: TGo4Analysis

Description:

Sets analysis step name as first one to be processed in the chain of steps. First step will read input event from its event source. If event source of new first step is not enabled, [InitEventClasses](#) will fail; except for the case when the consistency check of the analysis step was disabled by [SetStepChecking\(kFALSE\)](#). If name is nullpointer, set first step in steplist as first active step. This method is for setting up the analysis before initialization only, it should not be invoked on the fly!

Arguments:

const char* name Name of the analysis step to set first..

Return value:

Bool_t Is kFALSE in case of error (e.g. step not found).

Visibility:

public

Example of usage:

```
//... perform analysis with old setup here
CloseAnalysis() // close all files, delete old eventclasses
TGo4FileSourceParameter* spar2 =
    new TGo4FileSourceParameter ("raw.root");
NewStepSource("Calibrate", spar2); // setup input for second step
SetFirstStep("Calibrate");
InitEventClasses();
```

SetKeepInputEvent (Bool_t val=kTRUE):

Classes: TGo4EventProcessor

Description:

Mark current input event of this processor's analysis step to be used again in the next analysis cycle, without invoking the Clear() and Fill() methods which would erase the previous contents. This provides a "1 to n" event building functionality. To be used if in-put event contains several output event data sets. Each time this method is called in event processor, the next analysis cycle will skip all previous analysis steps and will reprocess the input. Once all data of the input event have been processed, the keep input event mode can be reset and the framework will continue with a new event. The state of the output event can be checked by [IsKeepInputEvent\(\)](#).

Arguments:

Bool_t val Switches the keep input event on (true) or off (false)

Return value:

void

Visibility:

public

Example of usage:

```
if(/*some more data in input event for next output event*/)
    SetKeepInputEvent(kTRUE);
else
    SetKeepInputEvent(kFALSE);
```

SetKeepOutputEvent (Bool_t val=kTRUE):

Classes: TGo4EventProcessor

Description:

Mark current output event of this processor's analysis step to be used again in the next analysis cycle, without invoking the Clear() methods which would erase the previously written contents. This provides a "n to 1" event building functionality. To be used if several input events must be processed to gain one output event. Each time these methods are called in event processor, the next analysis cycle will skip all subsequent analysis steps and will continue filling the output event data. The state of the output event can be checked by [IsKeepOutputEvent\(\)](#).

Arguments:

Bool_t val Switches the keep input event on (true) or off (false)

Return value:

void

Visibility:

public

Example of usage:

```
if(/*output event requires more data from input to be complete*/)
    SetKeepOutputEvent(kTRUE);
else
    SetKeepOutputEvent(kFALSE);
```

SetLastStep (const char* name):**Classes:** TGo4Analysis**Description:**

Sets analysis step name as last one to be processed in the chain of steps. If name is nullpointer, set last step in steplist as last active step. This method is for setting up the analysis before initialization only, it should not invoked on the fly!

Arguments:

const char* name Name of the analysis step to set last.

Return value:

Bool_t Is kFALSE in case of error (e.g. step not found).

Visibility:

public

Example of usage:

```
//... perform analysis with old setup here
CloseAnalysis() // close all files, delete old eventclasses
SetLastStep("Unpack");
InitEventClasses();
```

SetMakeWithAutosave(Bool_t on)**Classes:** TGo4EventProcessor**Description:**

Enable or disable the use of previous data from an Autosave file in methods [MakeTH1\(\)](#), [MakeTH2\(\)](#), [MakeWinCond\(\)](#), [MakePolyCond\(\)](#), [MakeParameter\(\)](#). By default using autosave is set.

Arguments:

Bool_t on If kTRUE (default), all *Make...* methods will deliver reference to previous object if existing. If kFALSE, there will always a new object be created.

Return value:

void

Visibility:

public

Example of usage:

```
SetMakeWithAutoSave(kFALSE);
fconHis1 = MakeWinCond("cHis1", 100, 2000, "His1");
```

SetParameter (const char* name, TGo4Parameter* par):**Classes:** TGo4Analysis**Description:**

Sets an already registered parameter of name to the values of the external parameter par. **Note that virtual method TGo4Parameter::UpdateFrom(TGo4Parameter*) must be implemented correctly in user parameter subclasses to let this work!** If parameter of given name is not existing in the folder, a copy of the external parameter par is registered instead of updating the old parameter.

Arguments:

const char* name	Name of the registered parameter under folder Go4/Parameters. Optionally, the string name may contain a subfolder name that proceeds the parameter name and is separated by a slash "/". Then parameter is searched in that subfolder of Go4/Parameters.
TGo4Parameter* par	Pointer to external parameter that contains the values for updating the registered parameter. Note that this external parameter is never adopted by framework! If parameter of name does not exist, a new parameter of the name will be created, updated from con and registered.

Return value:

Bool_t:	kTRUE if par was registered and set correctly.
---------	--

Visibility:

public

Example of usage:

```
TUserParameter* upara= new TUserParameter("ADC1Cal",0.42,132);
SetParameter("ADC2Cal",upara);
```


SetPicture (const char name, TGo4Picture* pic):*

Classes: TGo4Analysis

Description:

Sets an already registered picture of name to the values of the external picture pic. If picture of given name is not existing in the folder, a copy of the external picture par is registered instead of updating the old picture.

Arguments:

const char* name	Name of the registered picture under folder Go4/Pictures. Optionally, the string name may contain a subfolder name that proceeds the picture name and is separated by a slash "/". Then picture is searched in that subfolder of Go4/Pictures.
TGo4Picture* pic	Pointer to external picture that contains the values for updating the registered picture. Note that this external picture is never adopted by framework! If picture of name does not exist, a new picture of the name will be created, updated from pic and registered.

Return value:

Bool_t: kTRUE if pic was registered and set correctly.

Visibility:

public

Example of usage:

```
TGo4Picture* mypic= new TGo4Picture("frame5","E1-E4");  
SetPicture("frame3",mypic);
```

SetRunning(Bool_t on):

Classes: TGo4Analysis

Description:

Change the "running" state of the analysis slave as controlled from the GUI. To be used from ROOT macro in a Go4 CintServer environment to change the run status. Useful to react on analysis conditions checked in the running macro. **Note that from compiled code, it is rather recommended to throw a TGo4UserException with a message and error priority to halt analysis processing.**

Arguments:

Bool_t: If kTRUE, start processing; otherwise stop it.

Return value:

void

Visibility:

public

Example of usage:

```
if(!wincon->Test(mylimit)) SetRunning(kFALSE) ;
```

SetStepChecking (Bool_t on):**Classes:** TGo4Analysis**Description:**

Enables/Disables the consistency check of the analysis steps. By default, the input event of each step is checked if it matches the output event of the previous step with respect to class name and object name. Furthermore, the first active step must have an eventsource existing, and it is not possible to deactivate the processing of steps in between two active steps. This behaviour can be changed for analyses with more complex step structure (i.e. subsequent steps may not depend on the very previous step, but get input from other previous steps, or they may perform logically parallel parts of the analysis). In this case, the checks for input consistency depend on the user code.

Arguments:

Bool_t on	If kTRUE (default), steps consistency is checked. If kFALSE, steps are processed without checks from the framework.
-----------	---

Return value:

void

Visibility:

public

Example of usage:

```
SetStepChecking(kFALSE) ;
```

SetStepStorage (const char* name, Bool_t on):**Classes:** TGo4Analysis**Description:**

Switches the eventstore output of analysis step “name” on or off. Step must have an implemented eventstore instance

Arguments:

const char* name	Name of the analysis step.
Bool_t on	If kTRUE (default), storage will be switched on. If kFALSE, eventstore is disabled.

StoreCondition(const char stepname, TGo4Condition* con):*

Classes: TGo4Analysis

Description:

Saves condition con into the eventstore of analysis step stepname. Eventstore must have the virtual *Store(TGo4Condition*)* method implemented for this purpose. Current eventnumber will be added to the object name in the file (in case of TGo4FileStore). Useful for logging analysis parameters in the same file with the event output.

Arguments:

const char* stepname	Name of the analysis step the eventstore of which is used for saving the condition.
TGo4Condition* con	Pointer to condition that shall be saved.

Return value:

Int_t result -1= eventstore not active, +1= step not found, 0=OK.

Visibility:

public

Example of usage:

```
StoreCondition("Unpack", GetAnalysisCondition("wincon1"));
```

StoreFitter(const char stepname, TGo4Fitter* fit):*

Classes: TGo4Analysis

Description:

Saves fitter fit into the eventstore of analysis step stepname. Eventstore must have the virtual *Store(TGo4Fitter*)* method implemented for this purpose. Current eventnumber will be added to the object name in the file (in case of TGo4FileStore). Useful for logging analysis parameters in the same file with the event output.

Arguments:

const char* stepname	Name of the analysis step the eventstore of which is used for saving the fitter.
TGo4Fitter* fit	Pointer to fitter that shall be saved.

Return value:

Int_t result -1= eventstore not active, +1= step not found, 0=OK.

Visibility:

public

Example of usage:

```
StoreFitter("Unpack", fxCalibrationfitter);
```

StoreFolder(const char stepname, TFolder* fold):*

Classes: TGo4Analysis

Description:

Saves folder fold and all contained objects into the eventstore of analysis step stepname. Eventstore must have the virtual *Store(TFolder*)* method implemented for this purpose. Current eventnumber will be added to the object name in the file (in case of TGo4FileStore). Useful for logging analysis parameters in the same file with the event output.

Arguments:

const char* stepname	Name of the analysis step the eventstore of which is used for saving the folder.
TFolder* fold	Pointer to folder that shall be saved.

Return value:

Int_t result -1= eventstore not active, +1= step not found, 0=OK.

Visibility:

public

Example of usage:

```
StoreFolder("Analysis",GetObjectFolder());
```

StoreFolder(const char stepname, const char* foldername):*

Classes: TGo4Analysis

Description:

Saves registered go4 folder of name foldername and all contained objects into the eventstore of analysis step stepname. Eventstore must have the virtual *Store(TFolder*)* method implemented for this purpose. Current eventnumber will be added to the object name in the file (in case of TGo4FileStore). Useful for logging analysis parameters in the same file with the event output.

Arguments:

const char* stepname	Name of the analysis step the eventstore of which is used for saving the folder.
const char* foldername	Name of registered folder that shall be saved.

Return value:

Int_t result -1= eventstore not active, +1= step not found, 0=OK.

Visibility:

public

Example of usage:

```
StoreFolder("Analysis","MyAnalysisParameters");
```

StoreParameter(const char stepname, TGo4Parameter* par):*

Classes: TGo4Analysis

Description:

Saves parameter par into the eventstore of analysis step stepname. Eventstore must have the virtual *Store(TGo4Parameter*)* method implemented for this purpose. Current eventnumber will be added to the object name in the file (in case of TGo4FileStore). Useful for logging analysis parameters in the same file with the event output.

Arguments:

const char* stepname	Name of the analysis step the eventstore of which is used for saving the parameter.
TGo4Parameter* par	Pointer to parameter that shall be saved.

Return value:

Int_t result -1= eventstore not active, +1= step not found, 0=OK.

Visibility:

public

Example of usage:

```
StoreParameter("Analysis",GetParameter("Calibration"));
```

UserEventFunc():

Classes: TGo4Analysis

Description:

Virtual method to be overwritten in the user analysis subclass. **This function is called in the main analysis cycle from the framework, it should not be invoked from the user code!** Method is executed after each cycle of the analysis processing, i.e. after eventprocessor actions and dynamic list operations.

Arguments:

none

Return value:

virtual Int_t No effect.

Visibility:

public

Example of usage:

```
Int_t TEbAnalysis::UserEventFunc()  
{  
if(fxCaliEvent && fxCaliEvent->IsValid()) {  
    // Ge 1, 2, 3, 4 heavy particle on source side  
    Double_t dvalue= fxCaliEvent->fdNoOfCutH1;  
    if(dvalue>=1.0 && dvalue<=48.0)  
        fxGe1H1->Fill(fxCaliEvent->fdGammaH1);  
}  
return 0;  
}
```

UserPreLoop():

Classes: TGo4Analysis

Description:

Virtual method to be overwritten in the user analysis subclass. **This function is called in the main analysis cycle from the framework, it should not be invoked from the user code!** Method is called once before the analysis main loop, i.e. at the beginning of [RunImplicitLoop\(\)](#) in batch mode, or on pressing the “Start” button in gui mode, respectively.

Arguments:

none

Return value:

virtual Int_t No effect.

Visibility:

public

Example of usage:

```
Int_t TEBAnalysis::UserPreLoop()  
{  
    fxCaliEvent=dynamic_cast<TEbCalibratedEvent*>  
                (GetOutputEvent("Calibrate"));  
    return 0;  
}
```

UserPostLoop():

Classes: TGo4Analysis

Description:

Virtual method to be overwritten in the user analysis subclass. **This function is called in the main analysis cycle from the framework, it should not be invoked from the user code!** Method is called once after the analysis main loop, i.e. at the end of [RunImplicitLoop\(\)](#) in batch mode, or on pressing the “Stop” button in gui mode, respectively.

Arguments:

none

Return value:

virtual Int_t No effect.

Visibility:

public

Example of usage:

```
Int_t TEBAnalysis::UserPostLoop()  
{  
    fxCaliEvent=0; // reset pointer to event structure  
    AutoSave(); // save all objects each time analysis stops  
    return 0;  
}
```


2 GUI Macro Interface Documentation

2.1 Introduction

The class **TGo4AbstractInterface** provides the generic interface to the Go4 GUI functionality.

It provides methods like open file, request object from analysis, and so on.

Methods of that class can be used in an arbitrary ROOT script inside/outside Go4 GUI. To access these methods in a Go4 macro, one should use the "go4" variable which is exported to CINT global variable space when the instance of an TGo4AbstractInterface implementation class is created. One can also access such instance via **TGo4AbstractInterface::Instance()** static method.

There are two implementations of TGo4AbstractInterface class:

- TGo4Script - used together with Go4 GUI, created automatically when GUI started
- TGo4Interface - can be used in non GUI mode, must be created once by user

Because these are two implementations of the same interface, any macro which uses internally only the "go4" pointer should work similarly in both GUI and non GUI mode.

Typically one should use the interface as provided by that class, in a macro, executed inside the Go4 GUI. A simple example of such macro:

```
{
    go4->OpenFile("example.root");
    go4->DrawItem("example.root/hist1");
}
```

This macro opens a file from disk and displays one histogram from that file.

Most of the actions with objects work via the GUI object manager. Here each object (item) has an unique name, which includes full path to that object in the Go4 object hierarchy. In our example the item name is "example.root/hist1". To locate any object of a known name in the object hierarchy, one can use **FindItem()** method. In that case example will look like:

```
{
    go4->OpenFile("example.root");
    go4->DrawItem(go4->FindItem("hist1"));
}
```

There are several examples of GUI macros, which can be found in the \$GO4SYS/macros directory. Descriptions of each method can be seen further in this document. Since the "hot start" feature of Go4 is implemented by means of the *TGo4AbstractInterface* class, the user can produce *.hotstart files in Go4 GUI and take some generated code from it directly as starting point. For instance, how to display complex view panels, or how the analysis is configured and started with GUI functions..

2.2 TGo4AbstractInterface Class Reference

```
#include <TGo4AbstractInterface.h>
```

2.2.1 Public Member Functions

```
virtual ~TGo4AbstractInterface ()  
TGo4ObjectManager * OM () const  
TGo4BrowserProxy * Browser () const  
TGo4AnalysisProxy * Analysis ()  
virtual void HotStart (const char *filename)=0  
virtual void LoadLibrary (const char *fname)  
virtual void OpenFile (const char *fname)  
virtual TString FindItem (const char *objname)  
virtual Bool_t CopyItem (const char *itemname)  
virtual Bool_t DeleteItem (const char *itemname)  
virtual void FetchItem (const char *itemname, Int_t wait_time=2000)  
virtual TObject * GetObject (const char *itemname, Int_t updatelevel=1)  
virtual TString SaveToMemory (const char *path, TObject *obj, Bool_t ownership=kFALSE)  
virtual Bool_t SaveToFile (const char *itemname, const char *filename, const char *filetitle=0)  
virtual Bool_t ExportToFile (const char *itemname, const char *dirpath, const char *format, const char *filetitle=0)  
virtual void ConnectHServer (const char *servername, Int_t portnumber, const char *basename, const char  
    *userpass, const char *filter)  
virtual void ConnectDabc (const char *servername)  
virtual void ConnectHttp (const char *servername, , const char * account, const char * pass)  
virtual void Wait (double tm_sec)  
virtual void Message (const char *msg)  
virtual void LaunchAnalysis ()  
virtual void LaunchAnalysis (const char *ClientName, const char *ClientDir, const char *ClientExec, const char  
    *ClientNode, Int_t ShellMode=2, Int_t TermMode=1, Int_t ExeMode=0, const char *UserArgs=0)  
virtual void ConnectAnalysis (const char *ServerNode, Int_t ServerPort, Int_t UserMode, const char *password=0)  
virtual void WaitAnalysis (Int_t delay_sec)  
virtual Bool_t IsAnalysisConnected ()  
virtual void DisconnectAnalysis ()  
virtual void ShutdownAnalysis ()  
virtual void ExecuteLine (const char *remotecmd)  
virtual void RequestAnalysisConfig ()  
virtual void SubmitAnalysisConfig (int tmout=20)  
virtual void StartAnalysis ()  
virtual void StopAnalysis ()  
virtual void RefreshNamesList (int tmout=10)  
virtual void SetAnalysisTerminalMode (int mode)  
virtual void SetAnalysisConfigMode (int mode)  
virtual void MonitorItem (const char *itemname, Bool_t on=kTRUE)  
virtual void StartMonitoring (Int_t period=10)  
virtual void StopMonitoring ()  
virtual void AnalysisAutoSave (const char *filename, Int_t interval, Int_t compression, Bool_t enabled, Bool_t  
    overwrite)  
virtual void AnalysisConfigName (const char *filename)  
virtual void ConfigStep (const char *stepname, Bool_t enableprocess, Bool_t enablesource, Bool_t enablestore)  
virtual void StepFileSource (const char *stepname, const char *sourcename, int timeout)
```

virtual void [StepMbsFileSource](#) (const char *stepname, const char *sourcename, int timeout, const char *TagFile, int start=0, int stop=0, int interval=0)
 virtual void [StepMbsStreamSource](#) (const char *stepname, const char *sourcename, int timeout, int start=0, int stop=0, int interval=0)
 virtual void [StepMbsTransportSource](#) (const char *stepname, const char *sourcename, int timeout, int start=0, int stop=0, int interval=0)
 virtual void [StepMbsEventServerSource](#) (const char *stepname, const char *sourcename, int timeout, int start=0, int stop=0, int interval=0)
 virtual void [StepMbsRevServSource](#) (const char *stepname, const char *sourcename, int timeout, int port=0, int start=0, int stop=0, int interval=0)
 virtual void [StepMbsSelection](#) (const char *stepname, int start, int stop, int interval)
 virtual void [StepRandomSource](#) (const char *stepname, const char *sourcename, int timeout)
 virtual void [StepMbsPort](#) (const char *stepname, int port)
 virtual void [StepMbsRetryCnt](#) (const char *stepname, int cnt)
 virtual void [StepUserSource](#) (const char *stepname, const char *sourcename, int timeout, int port, const char *expr)
 virtual void [StepFileStore](#) (const char *stepname, const char *storename, bool overwrite, int bufsize, int splitlevel, int compression, int autosaveperiod=10000)
 virtual void [StepBackStore](#) (const char *stepname, const char *storename, int bufsize, int splitlevel)
 virtual void [SetMainWindowState](#) (int qtversion, const char *val)
 virtual void [SetMainWindowGeometry](#) (int qtversion, const char *val)
 virtual [ViewPanelHandle StartViewPanel](#) ()
 virtual [ViewPanelHandle StartViewPanel](#) (int x, int y, int width, int height, int mode=1, [TGo4Picture](#) *pic=0)
 virtual TString [GetViewPanelName](#) ([ViewPanelHandle](#) panel)
 virtual [ViewPanelHandle FindViewPanel](#) (const char *name)
 virtual Bool_t [SetViewPanelName](#) ([ViewPanelHandle](#) panel, const char *newname)
 virtual [ViewPanelHandle GetActiveViewPanel](#) ()
 virtual void [RedrawPanel](#) ([ViewPanelHandle](#) panel)
 virtual void [DivideViewPanel](#) ([ViewPanelHandle](#) panel, Int_t numX, Int_t numY)
 virtual TPad * [SelectPad](#) ([ViewPanelHandle](#) panel, Int_t number=0)
 virtual [TGo4Picture](#) * [GetPadOptions](#) ([ViewPanelHandle](#) panel, Int_t padnumber=0)
 virtual void [SetSuperimpose](#) ([ViewPanelHandle](#) panel, Bool_t on=kTRUE)
 virtual Bool_t [DrawItem](#) (const char *itemname, [ViewPanelHandle](#) panel=0, const char *drawopt=0)
 virtual void [RedrawItem](#) (const char *itemname)
 virtual const char * [GetDrawnItemName](#) ([ViewPanelHandle](#) panel, int cnt=0)
[ClassDef](#) ([TGo4AbstractInterface](#), 1)

2.2.2 Static Public Member Functions

static void [SetInitSharedLibs](#) (const char *libs=0)
 static [TGo4AbstractInterface](#) * [Instance](#) ()
 static void [DeleteInstance](#) ()
 static const char * [FileExtension](#) ()
 static Int_t [DelayMillisec](#) ()
[TGo4BrowserProxy](#) * [fBrowser](#)
[TList](#) [fxCommands](#)

2.2.3 Member Function Documentation

2.2.3.1 **virtual void TGo4AbstractInterface::AnalysisAutoSave (const char * *filename*, Int_t *interval*, Int_t *compression*, Bool_t *enabled*, Bool_t *overwrite*) [inline, virtual]**

Configure autosave properties of analysis

2.2.3.2 **virtual void TGo4AbstractInterface::AnalysisConfigName (const char * *filename*) [inline, virtual]**

Configure name of file, where analysis configuration will be saved

2.2.3.3 **TGo4BrowserProxy* TGo4AbstractInterface::Browser () const [inline]**

Returns pointer on browser proxy. TGo4BrowserProxy class provides complete interface to Go4 browser functionality. Should only be used when interface does not provide required functionality. Can be accessed directly via "br" variable.

2.2.3.4 **virtual void TGo4AbstractInterface::ConfigStep (const char * *stepname*, Bool_t *enableprocess*, Bool_t *enablesource*, Bool_t *enablestore*) [inline, virtual]**

Set basic step property

2.2.3.5 **virtual void TGo4AbstractInterface::ConnectAnalysis (const char * *ServerNode*, Int_t *ServerPort*, Int_t *UserMode*, const char * *password* = 0) [inline, virtual]**

Connect to running analysis server. Parameters: ServerNode - node to connect to, ServerPort - connection port number, UserMode - mode of user operation : 0 - observer, 1 - controller, 2 - administrator password - access password, which should correspond to specified UserMode

2.2.3.6 **void TGo4AbstractInterface::ConnectDabc (const char * *servername*) [virtual]**

Connect to DABC server. Address like dabc://host:port

**2.2.3.7 void TGo4AbstractInterface::ConnectHServer (const char *
servername, Int_t portnumber, const char * basename, const char *
userpass, const char * filter) [virtual]**

Connect to GSI histogram server. Creates appropriate entry in browser and provides access to histogram. Parameters: servername - IP server name portnumber - socket port number basename - histogram server base name userpass - password to access histogram server filter - filter for histograms names Several connections to different histogram servers are allowed

**2.2.3.8 virtual void TGo4AbstractInterface::ConnectHttp (const char *
servername, const char * account, const char * pass) [inline,
virtual]**

Connect to HTTP server. Address like <http://host:port/subfolder/> . authentication may be specified by username account and password pass

**2.2.3.9 Bool_t TGo4AbstractInterface::CopyItem (const char * itemname)
[virtual]**

Copy item to workspace. If there is subfolders with items, they also will be copied.

**2.2.3.10 const char * TGo4AbstractInterface::DefaultPicTitle () [static,
protected]**

Returns default hotstart file extension

2.2.3.11 Int_t TGo4AbstractInterface::DelayMillisec () [static]

Default delay during hotstart file extension

2.2.3.12 void TGo4AbstractInterface::DeleteInstance () [static]

Delete instance of interface class

**2.2.3.13 Bool_t TGo4AbstractInterface::DeleteItem (const char * itemname)
[virtual]**

Delete item (if allowed). Can be used to close file, delete memory object, close histogram server connection.

**2.2.3.14 virtual void TGo4AbstractInterface::DisconnectAnalysis ()
[inline, virtual]**

Disconnects from running analysis. If analysis is running in client mode, analysis will be shutdown.

**2.2.3.15 virtual void TGo4AbstractInterface::DivideViewPanel
(ViewPanelHandle panel, Int_t numX, Int_t numY) [inline,
virtual]**

Divide viewpanel on subpads.

**2.2.3.16 virtual Bool_t TGo4AbstractInterface::DrawItem (const char *
itemname, ViewPanelHandle panel = 0, const char * drawopt = 0)
[inline, virtual]**

Draw browser item on specified viewpanel. Parameters: itemname - browser item name, panel - viewpanel, if panel==0, new viewpanel will be created. drawopt - draw options, used in obj->Draw() operation

**2.2.3.17 void TGo4AbstractInterface::ExecuteLine (const char * remotecmd)
[virtual]**

Execute one macro line on analysis side. This allows to call any action on analysis, including execution scripts with ".x userscript.C". One should not mix scripts, written for analysis and scripts, written for GUI.

**2.2.3.18 Bool_t TGo4AbstractInterface::ExportToFile (const char * itemname,
const char * dirpath, const char * format, const char * filetype = 0)
[virtual]**

Export browser item to different file formats. One, probably, should use [FetchItem\(\)](#) before calling this method. If item is folder and contains sub-items, they also will be exported. Parameters: itemname - name of browser, which should be exported, dirpath - directory on disk, where files should be created. format - export file format, can be "ASCII" - text format "Radware" - Radware format (Origin) "ROOT" - binary ROOT format "ROOT XML" - xml ROOT format filetype - title of create file (only for ROOT formats)

**2.2.3.19 void TGo4AbstractInterface::FetchItem (const char * itemname, Int_t
wait_time = 2000) [virtual]**

Fetch item from data source. Request item from data source, to which item corresponds to. If this is file or histogram server, object will be returned immediately. If this is an item from analysis, first request will be send and then interface will wait "wait_time" milliseconds that object is arrived. If wait_time==0, no waiting will be done and most probably, new object will be assigned to that item several seconds after method is return

2.2.3.20 const char * TGo4AbstractInterface::FileExtension () [static]

Returns default hotstart file extension

**2.2.3.21 TString TGo4AbstractInterface::FindItem (const char * objname)
[virtual]**

Find item with given object name. Item name includes object name and name of all parent folders. For instance histogram of name "His1" in analysis will have item name "Analysis/Histograms/His1".

**2.2.3.22 virtual ViewPanelHandle TGo4AbstractInterface::FindViewPanel
(const char * name) [inline, virtual]**

Return handle on viewpanel with specified name.

2.2.3.23 virtual ViewPanelHandle

TGo4AbstractInterface::GetActiveViewPanel () [inline, virtual]

Return handle of last active viewpanel.

2.2.3.24 virtual const char* TGo4AbstractInterface::GetDrawnItemName (ViewPanelHandle panel, int cnt = 0) [inline, virtual]

Provide item name, drawn in the view panel. Optional cnt parameter could specify sequence number in panel, including all subpads

2.2.3.25 TObject * TGo4AbstractInterface::GetObject (const char * itemname, Int_t updatelevel = 1) [virtual]

Returns object, assigned to specified browser item. Parameter updatelevel specifies, how object will be requested from data source, to which item correspond to. Possible values for updatelevel parameter: 0 - no request will be done, return last requested object 1 - request to data source only first time, no waiting 2 - request to data source in any case, no waiting >9 - request to data source and wait as many milliseconds as specified by updatelevel Waiting required, when object requested from the analysis

2.2.3.26 virtual TGo4Picture* TGo4AbstractInterface::GetPadOptions (ViewPanelHandle panel, Int_t padnumber = 0) [inline, virtual]

Returns pad options for pad with specified number

2.2.3.27 virtual TString TGo4AbstractInterface::GetViewPanelName (ViewPanelHandle panel) [inline, virtual]

Return name of viewpanel.

2.2.3.28 virtual void TGo4AbstractInterface::HotStart (const char * filename) [pure virtual]

Executes hotstart file, generated in go4 GUI. Hot start files can not be executed as normal CINT scripts, therefore one should use this method to activate them

2.2.3.29 [TGo4AbstractInterface](#) * TGo4AbstractInterface::Instance () [static]

Return pointer on instance of implementation of [TGo4AbstractInterface](#) class Normally, inside CINT script one should use "go4" variable, which contains [TGo4AbstractInterface::Instance\(\)](#) value.

2.2.3.30 Bool_t TGo4AbstractInterface::IsAnalysisConnected () [virtual]

Indicate, if analysis was successfully connected

2.2.3.31 virtual void TGo4AbstractInterface::LaunchAnalysis () [inline, virtual]

Launch analysis in client mode, using default configuration. Can only work in standard GUI mode

2.2.3.32 virtual void TGo4AbstractInterface::LaunchAnalysis (const char * ClientName, const char * ClientDir, const char * ClientExec, const char * ClientNode, Int_t ShellMode = 2, Int_t TermMode = 1, Int_t ExeMode = 0, const char * UserArgs = 0) [inline, virtual]

Launch analysis in client mode. Parameters: ClientName - arbitrary name of analysis, used for display ClientDir - directory, where analysis should be started ClientExec - main analysis executable ClientNode - node name, where analysis should be started ShellMode - shell, used to launch analysis: 1 - rsh, 2 - ssh [default] TermMode - terminal program: 1 - internal Qt window, 2 - xterm, 3 - KDE konsole

2.2.3.33 void TGo4AbstractInterface::LoadLibrary (const char * fname) [virtual]

Load specified ROOT library

2.2.3.34 virtual void TGo4AbstractInterface::Message (const char * msg) [inline, virtual]

Display message in GUI status line

2.2.3.35 void TGo4AbstractInterface::MonitorItem (const char * itemname, Bool_t on = kTRUE) [virtual]

Enable/disable monitoring of browser item. In monitoring mode item regularly will be requested from analysis and viewpanels, where item is drawn, will be updated

2.2.3.36 TGo4ObjectManager* TGo4AbstractInterface::OM () const [inline]

Returns pointer on object manager. TGo4ObjectManager class should only be used when standard interface does not provide required functionality. Can be accessed directly via "om" variable.

2.2.3.37 void TGo4AbstractInterface::OpenFile (const char * fname) [virtual]

Open specified file in read-only mode* File and its structure should appear in browser.

2.2.3.38 void TGo4AbstractInterface::RedrawItem (const char * itemname) [virtual]

Redraw item of given name on all viewpanels/editors. Useful for the case, when content of object (histogram, for example) changed directly in script and after that should be updated in viewpanel.

2.2.3.39 virtual void TGo4AbstractInterface::RedrawPanel (ViewPanelHandle panel) [inline, virtual]

Forces of panel redraw.

2.2.3.40 virtual void TGo4AbstractInterface::RefreshNamesList (int *tmout* = 10) [inline, virtual]

Sends new request to the analysis and waits for new names list

2.2.3.41 void TGo4AbstractInterface::RequestAnalysisConfig () [virtual]

Requests current analysis configuration

2.2.3.42 Bool_t TGo4AbstractInterface::SaveToFile (const char * *itemname*, const char * *filename*, const char * *filetitle* = 0) [virtual]

Save specified browser item to file. Only object, which are already fetched from the data source, will be saved. Therefore, before one call this method, one probably should use [FetchItem\(\)](#) method to get objects from file/analysis/histogram server before save them. If item is folder and contains sub-items, they also will be saved. Only binary ROOT files (extension .root) and XML file (extension .xml) are supported.

2.2.3.43 TString TGo4AbstractInterface::SaveToMemory (const char * *path*, TObject * *obj*, Bool_t *ownership* = kFALSE) [virtual]

Save object in browser workspace. Object of any type can be saved in browser. It will appear in browser folder "Workspace", where local memory objects are placed. Parameters: path - subpath in "Workspace" folder, where object should be placed obj - pointer ob object ownership - is browser becomes owner of that object If item of that name exists in browser, it will be overwritten by new object Returns path to stored object in browser workspace

2.2.3.44 virtual TPad* TGo4AbstractInterface::SelectPad (ViewPanelHandle panel, Int_t *number* = 0) [inline, virtual]

Set active pad on viewpanel. If number==0, main pad (canvas) will be set as active, otherwise one of subpads will be activated. Most of methods, working with viewpanel, acting with active pad of this panel.

2.2.3.45 virtual void TGo4AbstractInterface::SetAnalysisConfigMode (int *mode*) [inline, virtual]

Set analysis configuration window mode. Parameters mode indicate that configuration window: -1 - closed, 0 - minimized, 1 - normal state

2.2.3.46 virtual void TGo4AbstractInterface::SetAnalysisTerminalMode (int *mode*) [inline, virtual]

Set analysis terminal window mode. Parameters mode indicate that terminal window: -1 - closed, 0 - minimized, 1 - normal state

2.2.3.47 void TGo4AbstractInterface::SetInitSharedLibs (const char * *libs* = 0) [static]

method to set initial list of shared libraries, which than will not be included in hostart file

2.2.3.48 virtual void TGo4AbstractInterface::SetMainWindowGeometry (int *qtversion*, const char * *val*) [inline, virtual]

Set geometry of main window

2.2.3.49 virtual void TGo4AbstractInterface::SetMainWindowState (int *qtversion*, const char * *val*) [inline, virtual]

Set state of all tool boxes in main window

2.2.3.50 virtual void TGo4AbstractInterface::SetSuperimpose (ViewPanelHandle *panel*, Bool_t *on* = kTRUE) [inline, virtual]

Set superimpose flag for active pad of viewpanel.

2.2.3.51 virtual Bool_t TGo4AbstractInterface::SetViewPanelName (ViewPanelHandle *panel*, const char * *newname*) [inline, virtual]

Change name of viewpanel.

2.2.3.52 virtual void TGo4AbstractInterface::ShutdownAnalysis () [inline, virtual]

Shutdown running analysis. If analysis is running in server mode, only user with administrator privileges can do this

2.2.3.53 virtual void TGo4AbstractInterface::StartAnalysis () [inline, virtual]

Starts (resume) analysis execution

2.2.3.54 void TGo4AbstractInterface::StartMonitoring (Int_t *period* = 10) [virtual]

Start monitoring mode. Parameter "period" specifies how often (in seconds) each monitored item will be updated.

2.2.3.55 virtual ViewPanelHandle TGo4AbstractInterface::StartViewPanel () [inline, virtual]

Create new view panel. Handle, returned by this method, must be used for other operation, like DivideViewPanel() or SelectPad()

2.2.3.56 virtual ViewPanelHandle TGo4AbstractInterface::StartViewPanel (int *x*, int *y*, int *width*, int *height*, int *mode* = 1, TGo4Picture * *pic* = 0) [inline, virtual]

Create new viewpanel with specified parameters. Returns handle of newly created viewpanel. Parameters: *x,y* - left top corner coordinate of view panel; *width, height* - panel size; *mode* - display view panel 0 - minimized, 1 - normal, 2 - maximized; *pic* - TGo4Picture object, which includes configuration of viewpanel. To understand usage of this method together with TGo4Picture class, one can create and configure viewpanel and then create hotstart file. This file will include complete TGo4Picture configuration, which contains attributes like colors, ranges, pad divisions and so on.

2.2.3.57 virtual void TGo4AbstractInterface::StepBackStore (const char * *stepname*, const char * *storename*, int *bufsize*, int *splitlevel*) [inline, virtual]

Set back store as step data storage

2.2.3.58 virtual void TGo4AbstractInterface::StepFileSource (const char * *stepname*, const char * *sourcename*, int *timeout*) [inline, virtual]

Set file source as step data source

2.2.3.59 virtual void TGo4AbstractInterface::StepFileStore (const char * *stepname*, const char * *storename*, bool *overwrite*, int *bufsize*, int *splitlevel*, int *compression*, int *autosaveperiod*=10000) [inline, virtual]

Set file as step data storage

2.2.3.60 virtual void TGo4AbstractInterface::StepMbsEventServerSource (const char * *stepname*, const char * *sourcename*, int *timeout*, int *start* = 0, int *stop* = 0, int *interval* = 0) [inline, virtual]

Set MBS event server as step data source

2.2.3.61 virtual void TGo4AbstractInterface::StepMbsFileSource (const char * *stepname*, const char * *sourcename*, int *timeout*, const char * *TagFile*, int *start* = 0, int *stop* = 0, int *interval* = 0) [inline, virtual]

Set MBS file source as step data source

2.2.3.62 virtual void TGo4AbstractInterface::StepMbsPort (const char * *stepname*, int *port*) [inline, virtual]

Set custom port number for MBS source like stream or transport server

2.2.3.63 virtual void TGo4AbstractInterface::StepMbsRetryCnt (const char * *stepname*, int *cnt*) [inline, virtual]

Set retry number for MBS source like stream or transport server

2.2.3.64 virtual void TGo4AbstractInterface::StepMbsRevServSource (const char * *stepname*, const char * *sourcename*, int *timeout*, int *port* = 0, int *start* = 0, int *stop* = 0, int *interval* = 0) [inline, virtual]

Set MBS remote event server as step data source

2.2.3.65 virtual void TGo4AbstractInterface::StepMbsSelection (const char * *stepname*, int *start*, int *stop*, int *interval*) [inline, virtual]

Set event selection for MBS source

2.2.3.66 virtual void TGo4AbstractInterface::StepMbsStreamSource (const char * *stepname*, const char * *sourcename*, int *timeout*, int *start* = 0, int *stop* = 0, int *interval* = 0) [inline, virtual]

Set MBS stream server as step data source

2.2.3.67 virtual void TGo4AbstractInterface::StepMbsTransportSource (const char * *stepname*, const char * *sourcename*, int *timeout*, int *start* = 0, int *stop* = 0, int *interval* = 0) [inline, virtual]

Set MBS transport server as step data source

2.2.3.68 virtual void TGo4AbstractInterface::StepRandomSource (const char * *stepname*, const char * *sourcename*, int *timeout*) [inline, virtual]

Set random generator as step data source

2.2.3.69 virtual void TGo4AbstractInterface::StepUserSource (const char * *stepname*, const char * *sourcename*, int *timeout*, int *port*, const char * *expr*) [inline, virtual]

Set user data source as step data source

2.2.3.70 virtual void TGo4AbstractInterface::StopAnalysis () [inline, virtual]

Stop (suspend) analysis execution

2.2.3.71 void TGo4AbstractInterface::StopMonitoring () [virtual]

Stop monitoring mode.

2.2.3.72 **virtual void TGo4AbstractInterface::SubmitAnalysisConfig (int *tmout* = 20) [inline, virtual]**

Submit configuration to analysis.

Configurations can be changed with following methods:

[AnalysisAutoSave\(\)](#);
[AnalysisConfigName\(\)](#);
[ConfigStep\(\)](#);
[StepFileSource\(\)](#);
[StepMbsFileSource\(\)](#);
[StepMbsStreamSource\(\)](#);
[StepMbsTransportSource\(\)](#);
[StepMbsEventServerSource\(\)](#);
[StepMbsRevServSource\(\)](#);
[StepRandomSource\(\)](#);
[StepUserSource\(\)](#);
[StepFileStore\(\)](#);
[StepBackStore\(\)](#).

To understand more how these methods can be used together, one should launch analysis, configure it and then generate hotstart file. In this file one can find correct sequence and parameters for all these methods. Timeout defines total time which will be required to get response from analysis that operation was completed.

2.2.3.73 **virtual void TGo4AbstractInterface::Wait (double *tm_sec*) [inline, virtual]**

Wait specified number of seconds. Suppress macro execution, but keeps GUI functional, therefore it is different from gSystem->Sleep() call.

2.2.3.74 **virtual void TGo4AbstractInterface::WaitAnalysis (Int_t *delay_sec*) [inline, virtual]**

Waits, until connection to analysis is established. Method must be called before any other action like configuration, start/stop can be done. If analysis is connected, [IsAnalysisConnected\(\)](#) return kTRUE. *delay_sec* specifies, how long one should wait until analysis is connected

3 Index

analysis loop	55
analysis server	30, 77
analysis step 7, 8, 19, 20, 21, 22, 23, 28, 29, 45, 46, 61, 62, 63, 66, 67, 68, 69, 70	
AnalysisAutoSave	
TGo4AbstractInterface	77
AnalysisConfigName	
TGo4AbstractInterface	77
autosave 7, 8, 10, 11, 12, 15, 26, 27, 31, 36, 37, 38, 39, 40, 41, 42, 43, 48, 58, 59, 60, 63, 77	
batch mode	7, 16, 25, 27, 55, 56, 71, 72
Browser	
TGo4AbstractInterface	77
canvas	8, 20, 52, 82
client mode	27, 28, 78, 81
condition.....	7, 9, 10, 14, 19, 36, 37, 38, 40, 43, 44, 48, 51, 57, 67, 68
ConfigStep	
TGo4AbstractInterface	77
ConnectAnalysis	
TGo4AbstractInterface	77
ConnectDabc	
TGo4AbstractInterface	77
ConnectHServer	
TGo4AbstractInterface	78
ConnectHttp	
TGo4AbstractInterface	78
CopyItem	
TGo4AbstractInterface	78
debug output	34
DefaultPicTitle	
TGo4AbstractInterface	78
DelayMillisec	
TGo4AbstractInterface	78
delete object.....	16
delete protected.....	16, 50
DeleteInstance	
TGo4AbstractInterface	78
DeleteItem	
TGo4AbstractInterface	78
DisconnectAnalysis	
TGo4AbstractInterface	78
DivideViewPanel	
TGo4AbstractInterface	78
DrawItem	
TGo4AbstractInterface	79
dynamic histogram	9
dynamic list	10, 49, 50, 52, 55, 60, 71
event object.....	20, 21, 22, 23
event objects	16, 22, 25, 31
event processor	7, 20, 25, 45, 62
event source.....	46, 61
event store.....	46
event structure	21, 22, 23, 67, 72
ExecuteLine	
TGo4AbstractInterface	79
export filter	18
ExportToFile	
TGo4AbstractInterface	79
FetchItem	
TGo4AbstractInterface	79
file format	18, 79
FileExtension	
TGo4AbstractInterface	79
FindItem	
TGo4AbstractInterface	79
FindViewPanel	
TGo4AbstractInterface	79
fitter.....	68
folder 7, 8, 9, 10, 11, 13, 14, 15, 16, 18, 20, 22, 25, 36, 37, 38, 39, 40, 41, 42, 43, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 64, 65, 67, 69, 79, 82	
framework..	7, 8, 10, 11, 12, 13, 16, 25, 26, 50, 51, 52, 53, 54, 55, 57, 62, 64, 65, 66, 71, 72
GetActiveViewPanel	
TGo4AbstractInterface	80
GetDrawnItemName	
TGo4AbstractInterface	80
GetObject	
TGo4AbstractInterface	80
GetPadOptions	
TGo4AbstractInterface	80
GetViewPanelName	
TGo4AbstractInterface	80
histogram ...	7, 9, 10, 11, 14, 18, 21, 36, 37, 38, 40, 41, 42, 43, 44, 49, 50, 53, 60, 74, 78, 79, 81, 82
HotStart	
TGo4AbstractInterface	80
Initialization	25
input file	26, 29, 46, 59
Instance	
TGo4AbstractInterface	80
IsAnalysisConnected	
TGo4AbstractInterface	80
LaunchAnalysis	
TGo4AbstractInterface	81
LoadLibrary	
TGo4AbstractInterface	81
logfile	32, 33, 34, 44
macro	30, 39, 50, 65, 73, 74, 79, 86
message	32, 33, 34, 44, 56, 65, 81
Message	
TGo4AbstractInterface	81
MonitorItem	
TGo4AbstractInterface	81
OM	
TGo4AbstractInterface	81
OpenFile	
TGo4AbstractInterface	81
parameter 12, 23, 39, 45, 46, 52, 54, 58, 64, 70, 80	
picture	12, 13, 24, 54, 65

RedrawItem		TGo4AbstractInterface	81
RedrawPanel		TGo4AbstractInterface	82
RefreshNamesList		TGo4AbstractInterface	82
RequestAnalysisConfig		TGo4AbstractInterface	82
SaveToFile		TGo4AbstractInterface	82
SaveToMemory		TGo4AbstractInterface	82
script	17, 18, 50, 73, 74, 80, 81		
SelectPad		TGo4AbstractInterface	82
SetAnalysisConfigMode		TGo4AbstractInterface	82
SetAnalysisTerminalMode		TGo4AbstractInterface	82
SetInitSharedLibs		TGo4AbstractInterface	83
SetMainWindowGeometry		TGo4AbstractInterface	83
SetMainWindowState		TGo4AbstractInterface	83
SetSuperimpose		TGo4AbstractInterface	83
settings	25, 31, 48, 56, 57		
SetViewPanelName		TGo4AbstractInterface	83
shaped condition	36, 37, 38		
ShutdownAnalysis		TGo4AbstractInterface	83
StartAnalysis		TGo4AbstractInterface	83
StartMonitoring		TGo4AbstractInterface	83
StartViewPanel		TGo4AbstractInterface	83, 84
StepBackStore		TGo4AbstractInterface	84
StepFileSource		TGo4AbstractInterface	84
StepFileStore		TGo4AbstractInterface	84
StepMbsEventServerSource		TGo4AbstractInterface	84
StepMbsFileSource		TGo4AbstractInterface	84
StepMbsPort		TGo4AbstractInterface	84
StepMbsRetryCnt		TGo4AbstractInterface	85
StepMbsRevServSource		TGo4AbstractInterface	85
StepMbsSelection		TGo4AbstractInterface	85
StepMbsStreamSource		TGo4AbstractInterface	85
StepMbsTransportSource		TGo4AbstractInterface	85
StepRandomSource		TGo4AbstractInterface	85
StepUserSource		TGo4AbstractInterface	85
StopAnalysis		TGo4AbstractInterface	85
StopMonitoring		TGo4AbstractInterface	85
SubmitAnalysisConfig		TGo4AbstractInterface	86
TCanvas	8, 20, 52		
TGo4AbstractInterface			75
AnalysisAutoSave			77
AnalysisConfigName			77
Browser			77
ConfigStep			77
ConnectAnalysis			77
ConnectDabc			77
ConnectHServer			78
ConnectHttp			78
CopyItem			78
DefaultPicTitle			78
DelayMillisec			78
DeleteInstance			78
DeleteItem			78
DisconnectAnalysis			78
DivideViewPanel			78
DrawItem			79
ExecuteLine			79
ExportToFile			79
FetchItem			79
FileExtension			79
FindItem			79
FindViewPanel			79
GetActiveViewPanel			80
GetDrawnItemName			80
GetObject			80
GetPadOptions			80
GetViewPanelName			80
HotStart			80
Instance			80
IsAnalysisConnected			80
LaunchAnalysis			81
LoadLibrary			81
Message			81
MonitorItem			81
OM			81
OpenFile			81
RedrawItem			81
RedrawPanel			82
RefreshNamesList			82
RequestAnalysisConfig			82
SaveToFile			82
SaveToMemory			82
SelectPad			82
SetAnalysisConfigMode			82
SetAnalysisTerminalMode			82
SetInitSharedLibs			83
SetMainWindowGeometry			83

SetMainWindowState	83	StepUserSource	85
SetSuperimpose	83	StopAnalysis	85
SetViewPanelName	83	StopMonitoring	85
ShutdownAnalysis	83	SubmitAnalysisConfig	86
StartAnalysis	83	Wait	86
StartMonitoring	83	WaitAnalysis	86
StartViewPanel	83, 84	TGo4AnalysisStep	20
StepBackStore	84	TGo4Condition	7, 19, 48, 57, 68
StepFileSource	84	TGo4EventElement	20, 21, 22, 23, 67
StepFileStore	84	TH1	10, 15, 18, 21, 41, 57
StepMbsEventServerSource	84	TH2	42
StepMbsFileSource	84	tree	13, 14, 24, 25, 55, 60
StepMbsPort	84	TTree	9, 10, 13, 14, 25, 55, 60, 67
StepMbsRetryCnt	85	user analysis	7, 16, 25, 55, 71, 72
StepMbsRevServSource	85	Wait	
StepMbsSelection	85	TGo4AbstractInterface	86
StepMbsStreamSource	85	WaitAnalysis	
StepMbsTransportSource	85	TGo4AbstractInterface	86
StepRandomSource	85		